

United States Patent Application for:

Haptic Interface for Palpation Simulation

Inventors:

- | | |
|---|---|
| 1) Richard L. Cunningham
1423 36 th St. NW
Washington, DC 20007; | 4) Gregory L. Merrill
4822 Leland St
Chevy Chase, MD 20815; |
| 2) Robert F. Cohen
3827 Gateway Terrace
Burtonsville, MD 20866; | 5) Philip G. Feldman
205 Newburg Ave.
Catonsville, MD 21228 |
| 3) Russell H. Dumas
12340 Quail Woods Drive
Germantown, MD 20874 | 6) Joseph L. Tasto
18748 Tanterra Way
Brookeville, MD 20833 |

Assignee: Immersion Medical, Inc.
Entity: Large Entity
Docket No.: IMD008


CERTIFICATE OF EXPRESS MAILING:

"Express Mail" mailing label number EK860304995US

Date of Deposit May 4, 2001

I hereby certify that this paper is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to: Commissioner for Patents, Washington, D.C. 20231.

Guy V. Tucker
Name of Person Mailing Paper


Signature of Person Mailing Paper

Haptic Interface for Palpation Simulation

BACKGROUND

5 The present invention relates to interfacing a user with a computer, such as a computer for performing a medical training simulation.

10 Medical practitioners often provide hands-on medical care. For example, a physician, nurse, care-giver, or other individual may need to perform a touch-related procedure on a patient. In these touch-related procedures, the medical practitioner uses a body part, such as one or more fingers or hands, to contact a surface on or in a body of a patient. The medical practitioner then may use his or her sense of touch to assess a condition of the patient or to treat the patient. One touch-related diagnostic procedure is palpation. Palpation relates to a physical examination with one or more fingers, hands or other body part to feel or detect by the sense of touch a condition of the body or the location of a part of the body. A palpation procedure may be performed by a medical practitioner to make a locative determination, to make a diagnostic assessment, and/or to therapeutically treat the patient. For example, by properly palpating a region, the medical practitioner can locate a feature, such as a vein, artery, lymph node, organ, cellular abnormality, bone or other hard tissue, or other feature, underlying the skin in that region. By careful feeling of a feature, the medical practitioner can make objective or subjective determinations of abnormal conditions. Also, a medical practitioner or other person can use palpation to perform a vascular assessment on a patient. Vascular assessment procedures, such as pulse rate, pulse strength, thrill detection, etc., provide the medical practitioner with a preliminary determination of a vascular condition.

25 The effectiveness of a palpation procedure is dependent on the skill of the person performing the procedure. However, palpation is a difficult procedure to train. Typically, the medical practitioner is trained clinically, through direct contact with patients. Early in the trainee's career, the likelihood of judgmental errors or diagnostic oversights may be high due to the medical practitioner's limited palpation experience. Even when properly supervised, training on actual patients is less than desirable since the trainee is unable to experiment and explore without risking injury to the patient. In addition, it is difficult to expose even experienced medical practitioners with uncommon palpation scenarios or with rare abnormalities.

To lessen the amount of training on actual patients, training simulators have been developed. In one training simulator, a physical mannequin is used to train the medical practitioner in performing a touch-related procedure. However, the physical mannequin can be cumbersome and difficult to manufacture. Additionally, the physical mannequin is limited in the number of situations that can be demonstrated. Another training simulator consists of a computer simulation of a patient's pulse. However, this computer simulator does not provide the trainee with a simulation of the feel of the procedure. Instead, the computer merely provides visual and/or audible pulsation feedback to the trainee. Thus, the trainee does not come away from the simulation having experienced the procedure through his or her sense of touch, nor does the computer simulator of pulse allow for the simulation of other palpation related procedures.

SUMMARY

To overcome the deficiencies of the prior art, it is desirable to be able to simulate a touch-related procedure in a way that is experienced through a user's sense of touch. It is further desirable to provide a haptic simulation of a touch-related procedure, such as a palpation procedure. It is also desirable to provide a realistic simulation of a touch-related procedure using a compact and easily portable simulator.

The present invention satisfies these needs. In one aspect of the invention, a method for interfacing a user with a computer running an application program, the computer generating a graphical environment comprising a cursor and a graphical representation of at least a portion of a living body, comprises providing an object in communication with the computer, controlling the cursor in relation to manipulation of at least a portion of the object by the user, and outputting a haptic sensation to the user when the cursor interacts with a region within the graphical representation to provide the user with haptic feedback related to a simulated palpation of the region.

In another aspect of the invention, a method for interfacing a user with a computer running an application program, the computer generating a graphical environment comprising a cursor and a graphical representation of at least a portion of a living body, comprises providing an object in communication with the computer, controlling the cursor in

relation to manipulation of at least a portion of the object by the user, and outputting a haptic sensation to the user when the cursor interacts with the graphical representation to simulate a pulse of the living body.

5 In another aspect of the invention, a method for interfacing a user with a computer running an application program, the computer generating a graphical environment comprising a cursor and a graphical representation of at least a portion of a living body, comprises providing an object in communication with the computer, controlling the cursor in relation to manipulation of at least a portion of the object by the user, and outputting a haptic
10 sensation to the user when the cursor interacts with the graphical representation to simulate a palpated feature on or below the surface of the graphical representation.

In another aspect of the invention, a palpation simulator comprises a computer readable medium comprising a computer readable program including program instructions to
15 cause a palpation simulation to be executed on a computer, and to cause the computer to generate a cursor and a graphical representation of at least a portion of a living body, an object in communication with the computer, at least a portion of the object being manipulatable by a user, a sensor in communication with the computer and coupled to the object to detect a manipulation of the at least a portion of the object to control the cursor, and an actuator coupled
20 to the object to output a haptic sensation to the user when the cursor interacts with a region within the graphical representation, the haptic sensation simulating a palpation of the living body.

DRAWINGS

25 These features, aspects, and advantages of the present invention will become better understood with regard to the following description, appended claims, and accompanying drawings which illustrate exemplary features of the invention. However, it is to be understood that each of the features can be used in the invention in general, not merely in the context of the
30 particular drawings, and the invention includes any combination of these features, where:

Figure 1 is a schematic view of a simulation system according to the present invention;

Figures 2A-2D are examples of graphical environments that may be generated by versions of the simulation system of the present invention;

Figure 3 is a graphical environment generated by a version of a pulse training simulation system;

Figure 4 is a graphical environment generated by a version of a palpation training simulation system;

Figure 5 is a schematic perspective view of a mouse device which may be used as a haptic interface in a simulation system according to the present invention;

Figure 6 is a schematic side view of an embodiment of a tactile mouse that may be used as a haptic interface in a simulation system according to the present invention;

Figure 7 is a schematic side view of another embodiment of a tactile mouse that may be used as a haptic interface in a simulation system according to the present invention;

Figure 8 is a schematic side view of another embodiment of a tactile mouse that may be used as a haptic interface in a simulation system according to the present invention;

Figure 9 is a block diagram schematically illustrating a version of a simulation system with a tactile mouse;

Figure 10 is a schematic perspective view of a kinesthetic force feedback mouse that may be used as a haptic interface in a simulation system according to the present invention;

Figures 11A, 11B, and 11C are schematic perspective views of the kinesthetic force feedback mouse of Figure 10 showing the electronic and mechanical interfaces of the mouse and a platform for the mouse;

Figure 12 is a block diagram schematically illustrating a version of a simulation system with a kinesthetic force feedback mouse;

Figure 13A is a schematic illustrating a graphical representation that may be generated by a simulation system;

Figure 13B shows a haptic sensation force profile associated with the graphical representation of Figure 13A;

Figure 13C is a schematic illustrating another graphical representation that may be generated by a simulation system;

Figure 13D shows a haptic sensation force profile associated with the graphical representation of Figure 13C;

Figure 14A is a schematic illustrating a graphical representation of a body part that may be generated by a simulation system;

Figure 14B shows a haptic sensation force profile associated with the graphical representation of Figure 14A;

Figure 15A is a schematic illustrating a graphical representation of a body part with an underlying feature that may be generated by a simulation system;

Figures 15B-D show haptic sensation force profiles associated with the graphical representation of Figure 15A, each corresponding to different z-axis forces applied by a user; and

Figure 16 is a version of a mouse that may be used with the simulation system according to the present invention.

DESCRIPTION

The present invention relates to computer simulations and more particularly to computer simulations involving haptic feedback. Although the process is illustrated in the context of medical training simulations, the present invention can be used in other simulation and computer interactive processes and should not be limited to the examples provided herein.

Figure 13A is a schematic illustrating a graphical representation that may be generated by a simulation system;

Figure 13B shows a haptic sensation force profile associated with the graphical representation of Figure 13A;

Figure 13C is a schematic illustrating another graphical representation that may be generated by a simulation system;

Figure 13D shows a haptic sensation force profile associated with the graphical representation of Figure 13C;

Figure 14A is a schematic illustrating a graphical representation of a body part that may be generated by a simulation system;

Figure 14B shows a haptic sensation force profile associated with the graphical representation of Figure 14A;

Figure 15A is a schematic illustrating a graphical representation of a body part with an underlying feature that may be generated by a simulation system;

Figures 15B-D show haptic sensation force profiles associated with the graphical representation of Figure 15A, each corresponding to different z-axis forces applied by a user; and

Figure 16 is a version of a mouse that may be used with the simulation system according to the present invention.

DESCRIPTION

The present invention relates to computer simulations and more particularly to computer simulations involving haptic feedback. Although the process is illustrated in the context of medical training simulations, the present invention can be used in other simulation and computer interactive processes and should not be limited to the examples provided herein.

Figure 1 is a schematic illustration of a simulation system **100** according to the invention. A display **105** provides a graphical environment **110** to a user. Within the graphical environment **110** is a cursor **115**, such as the arrow cursor shown in Figure 1. By cursor it is meant any cursor or object, the position, movement, shape, or the like of which is controllable. Also within the graphical environment **110** is a graphical representation **120** such as a graphical representation of at least a portion of a living body. For example, the graphical representation **120** may comprise a human body, a portion of a human body, an animal body, or a portion of an animal body. A controller **125** in communication with the display **105** is capable of generating and/or controlling the graphical environment **110**. A user object **130** is manipulatable by a user, and the manipulation of the user object **130** controls the position of the cursor **115** within the graphical environment **110**, for example by directly correlating a position of the user object **130** with a displayed position of the cursor **115** or by correlating a position of the user object with a rate of movement of the cursor **115**. Either the entire user object **130** may be manipulatable by the user or a portion of the user object **130** may be manipulatable relative to another portion of the user object **130**. For example, the user object may be a surface that is engaged by one or more hands of a user, such as a joystick, a mouse, a mouse housing, a stylus, a knob, an elongated rigid or flexible member, an instrumented glove, or the like and may be moveable in from one to six degrees of freedom or more.

When a predetermined event occurs within the graphical environment **110**, such as an interaction of the cursor **115** with the graphical representation **120**, the controller **125** causes an actuator **135** to output a haptic sensation to the user. In the version shown, the actuator **135** outputs the haptic sensation to the user object **130** through which the sensation is provided to the user. In the version shown, the actuator **135** and the user object **130** are part of a haptic interface device **140**. The actuator **135** may be positioned in the haptic interface device **140** to apply a force to the user object **130** or to a portion of the user object. For example, the haptic interface device **140** may comprise a user object **130**, such as a mouse housing, having an actuator **135** within the user object **130**, such as a vibrating motor within the mouse housing, or the haptic interface device may comprise a user object **130**, such as a mouse, that is mechanically linked to an actuator **135**.

The actuator **135** may provide the haptic sensation actively or passively. For example, the actuator **135** may comprise one or more motors coupled to the user object **130** to

apply a force to the user object **130** in one or more degrees of freedom. Alternatively or additionally, the actuator **135** may comprise one or more braking mechanisms coupled to the user object to inhibit movement of the user object **130** in one or more degrees of freedom. By haptic sensation it is meant any sensation provided to the user that is related to the users sense of touch. For example, the haptic sensation may comprise kinesthetic force feedback and/or tactile feedback. By kinesthetic force feedback it is meant any active or passive force applied to the user to simulate a force that would be experienced in the graphical environment **110**, such as a grounded force applied to the user object **130** to simulate a force acting on at least a portion of the cursor **115**. For example, if the cursor **115** is positioned against a surface, a barrier, or an obstruction, the actuator **135** may output a force against the user object **130** preventing or retarding movement of the user object **130** in the direction of the surface, barrier or, obstruction. By tactile feedback it is meant any active or passive force applied to the user to provide the user with a tactile indication of a predetermined occurrence within the graphical environment **110**. For example, a vibration, click, pop, or the like may be output to the user when the cursor **115** interacts with a graphical object. Additionally, tactile feedback may comprise a tactile sensation applied to approximate or give the illusion of a kinesthetic force. For example, by varying the frequency and/or the amplitude of an applied vibration, variations in surface textures of different graphical objects can be simulated, or by providing a series of clicks when a cursor penetrates an object, resistance to the penetration can be simulated. In one exemplary version, a kinesthetic force sensation, such as a spring force, may be applied to the user whenever the cursor **115** engages the graphical representation **120** to simulate a selectively deformable surface. Alternatively or additionally, a tactile sensation, such as a pop, may be applied to the user when the cursor **115** is moved across a surface of the graphical representation **120** to simulate a texture of the graphical representation **120**.

The simulation system **100** may, in one version, perform a medical simulation. The medical simulation may be a virtual reality simulation where the user interacts with the graphical environment **110** by manipulation of the user object **130** and by receiving visual, audible, and/or haptic feedback of the interaction. In the version shown in Figure 1, haptic feedback is output to the user in response to a predetermined interaction between the cursor **115** and the graphical representation **120**. For example, when user object **130** is manipulated so as to cause the cursor **115** to be positioned on or in contact with the graphical representation **120**, a haptic sensation is provided by the actuator **135** to the user object **130** in accordance with program code within or in communication with the controller **125**. The simulation system **100**

may simulate a touch-related procedure. During the touch-related procedure, the user may be provided with a haptic sensation related to the simulation of touch interaction of the user with the graphical representation **120**.

5 A haptic sensation may be applied to the user when the cursor **115** interacts with the graphical representation **120** or with a portion of the graphical representation **120**. For example, as shown in Figure 2A, the graphical representation **120** may comprise one or more first regions **150**. When the cursor **115** interacts with a first region **150**, such as by being positioned within or adjacent to the first region **150**, a haptic sensation is applied to the user.

10 The one or more first regions **150** may or may not be displayed to the user in the graphical environment **110**. In addition, the graphical representation **120** may comprise one or more second regions, the simulation system being adapted to apply a second haptic sensation to the user with the cursor **115** interacts with the second region. The version of Figure 2B shows a second region comprising the portion **155** of the graphical representation **120** other than the first region **150**. In Figure 2C, the second region is a portion **160** at least partially surrounding the first region **150**. Alternatively, the second region may comprise a region **165** within the graphical representation **120** spaced from the first region **150**.

15

20 In one version, the simulation system **100** may allow a user, such as a medical practitioner trainee, to simulate palpation of a living body. By palpation it is meant any therapeutic, diagnostic or other procedure where a medical practitioner contacts a patient with a portion of the medical practitioner's body, such as one or more fingers and/or hands, and utilizes his or her sense of touch to treat, diagnose or otherwise care for or administer to the patient. A medical practitioner may use palpation to locate and/or evaluate exterior or interior anatomical features or masses in or on the patient's body. For example, the medical practitioner may feel for organs or other tissues, cellular masses, abnormalities, vascular conditions, bone conditions, vibrations of the chest, etc. The vascular conditions may be conditions related to the flow of blood in the patient, such as pulse rate or strength, or other blood flow conditions, such as vascular thrill.

25

30 The simulation system **100** may, in one version comprise a palpation trainer. In this version, the controller **125** or other device may be capable of executing an application program comprising palpation training program code. The palpation training program is designed to configurably instruct a trainee on proper palpation techniques and/or to present the

trainee with various palpation scenarios. The palpation training program may control the output of haptic sensations to the user of the simulation system **100** to provide the user with an immersive experience that allows the user to learn the palpation procedure through his or her sense of touch. This is advantageous over prior trainers or classrooms which attempt to train medical practitioners visually or audibly rather than by training through the actual sense that the medical practitioner will have to use when performing actual palpation procedures on actual patients. The palpation trainer according to the invention is also advantageous over mannequin trainers in its economy of size and space and in that the scenarios that may be generated are more numerous than in a mechanical model. In addition, the use of the simulation system **100** is advantageous over a clinical setting since the trainee may experiment with, for example, how hard to press or in what areas to press or feel without the fear of injuring or causing discomfort to a patient.

The simulation system **100** comprising a palpation training program may generate a graphical environment **110**, such as the graphical environment shown in Figure 1. The palpation program may cause the simulation system **100** to task the user to position the cursor **115** at a target, which may or may not be displayed to the user, on or near the graphic representation **120**. For example, the tasking may comprise the presentation of a visual or an audible instruction to the user. Alternatively, an instructor may task the user. As the user causes the cursor **115** to interact with the cursor **120**, the simulation system causes a haptic sensation to be output to the user. In a simple form, a tactile cue, such as a pop, is output to the user when the cursor **115** intersects a boundary of the graphical representation **120**. This relatively simple version allows the user to interact with the simulation system **100** and to receive information through the user's sense of touch. As a result, the user utilizes the sense, i.e. the sense of touch, that the user will use during actual palpation procedures on a patient, thus creating a more authentic simulation.

In another version, a haptic sensation may be output to a user when the user causes the cursor **115** to interact with the graphical representation **120** in a predetermined manner. For example, the target to which the user is tasked to locate, may be associated with a region of the graphical representation **120**, such as the first region **150** shown in Figure 2A. In this version, the simulation system **100** may provide a haptic sensation, such as a tactile sensation, when the cursor **115** has been located at or is within a predetermined distance of the target. This provides an authentic simulation that trains the user to concentrate on touch input at

or near a targeted area. To further create an authentic simulation, a first haptic sensation may be output to the user when the cursor **115** interacts with the first region **150** and a second haptic sensation may be output to a user when the cursor **115** interacts with a second region on the graphical representation **120**. For example, a first haptic sensation may indicate to the user that the target has been located and the second haptic sensation may indicate that a non-targeted area of the graphical representation **120** is being interacted with. For example, as shown in the schematic of the graphical environment **110** in Figure 2B, the second haptic sensation may be output when the cursor **115** intersects the portion **155** other than the first region **150** and may be indicative of the interaction of the cursor **115** with, for example, the skin, such as by presenting a texture sensation or a deformable surface sensation. In another version, as shown in Figure 2C, the second haptic sensation may be applied when the cursor **115** interacts with a region **160** near the first region **150**, for example, by presenting a scaled version of the haptic sensation output when the cursor **115** is in the first region **150**. In the version of Figure 2D, the second haptic sensation may be applied when the cursor **115** interacts with a portion **165** spaced from the first region **150**. The second haptic sensation may be associated with a second targeted area or may be a scaled version of the first haptic sensation. In any of the versions shown in Figures 2A through 2D, third, fourth, fifth, etc. haptic sensations may be associated with predetermined regions of the graphical representation to further increase the authenticity of the simulation. For example, in the version of Figure 2C, a skin texture haptic sensation may be applied when the cursor **115** intersects the graphical representation **120** outside the first region **150** or the surrounding region **160**.

In a particular example of the simulation system **100**, the simulation system **100** may comprise a palpation trainer adapted to train a user to properly locate and/or evaluate a blood flow condition, such as a pulse of a living body. Pulse is the rhythmical expansion and contraction of an artery that can be felt near the surface of a body. The rate, strength and regularity of the pulse may be an indication of the pumping action of the heart and may vary with age and/or activity. For example, the pulse rate of a young baby may be as high as 120 to 140 beats per minute and may be on average about 70 beats per minute for a resting adult. A trained athlete at the extreme of physical effort may have a pulse rate of up to 180 beats per minute, with a resting pulse rate of less than 60 beats per minute. Any of these conditions may be simulated by the simulation system **100**. Certain determinations can be made from an evaluation of a pulse. For example, an ectopic beat, or a missed beat, may be sensed by evaluating a pulse. This may provide an indication some underlying form of heart disease.

Also, rapid pulse rates, also known as tachycardia, and slow pulse rates, also known as bradycardia, may be detected. Irregular pulse rates may be an indication of atrial fibrillation.

In one version of the pulse trainer, the first region **150**, as shown for example in Figure 2A, may be representative of an area on the graphical representation **120** where a pulse may be felt by a user. The haptic sensation associated with the first region **150** may be a tactile sensation simulating the feel of a pulse. For example, the user object **130** may output to the user a vibration having a repeating waveform and having a predetermined amplitude and frequency to simulate the sensation of a pulse. The amplitude may be variable and may be a function of the position of the cursor **115**. For example, the amplitude may be at a maximum at the center of the first region **150** and may diminish as the cursor position approaches the periphery of the first region **150**. In another version, as shown for example in Figure 2C, a first amplitude may be associated with the first region **150** and a second amplitude may be associated with the surrounding region **160**.

In use, the pulse trainer may task the user to find and/or take the pulse of an individual represented by the graphical representation **120**. A portion of the living body may then be displayed and the user may be tasked with positioning the cursor **115** at a pulse taking location. In one version, a user may be tasked with precisely locating a specific pulse-taking location. For example, as shown in Figure 2A, a forearm of a simulated patient may be displayed as the graphical representation **120** and within the forearm representation may be nested a region **150** corresponding to a position in the wrist area where the pulse can be detected from the radial artery. The pulse trainer may then instruct the user to locate a position where the pulse may be taken from the radial artery. When the user correctly locates the region **150** a haptic sensation indicating to the user the pulse has been correctly located and/or simulating a pulse sensation may be output to the user. Alternatively or additionally, a user may be tasked with more general instructions, such as “locate a pulse.” In one version, two or more pulse locating areas may be within the graphical representation **120**. For example, as shown in the version of Figure 2D, a first region **150** may be associated with a radial artery pulse taking location and a second region **165** may be associated with a brachial artery pulse taking location. The user may then locate the pulse at either location. The haptic sensation may be the same for the different regions or may vary, for example by varying in magnitude. In this version, the user may be taught through the sense of touch which pulse taking regions are best for a given orientation of the body or body shape.

The pulse trainer may present one or more training scenarios which present to the user one or more haptic sensations associated with the pulse or with another blood flow condition. For example, for beginners, the simulation system **100** may visually or audibly provide the user information such as or similar to: “Learning to take a pulse: You can feel a pulse at many locations where an artery is positioned close to an outer surface of a body. The pulse is particularly easy to feel in positions where the artery lies across a bone. The usual place to take a patient's pulse is at the wrist. Place the first and second fingers of your hand gently on the patient's wrist about 1 inch (2.5cm) above the base of the thumb. After a few seconds, you should feel the beats of the pulse through the radial artery. Count the number of beats during one full minute by watching the second hand of a clock or wristwatch. Alternatively count the number of beats for 15 seconds and multiply the number of counted beats by four.” In conjunction with this, the user may position the cursor **115** at the patient’s wrist and receive a corresponding haptic sensation, such as a low frequency vibration simulating a pulse. The pulse sensation may be applied immediately or may be delayed. In another version, the haptic device **140** is caused to physically move or guide the user to the correct location by the simulation system **100** to provide initial training . Alternatively or additionally, the simulation system **100** may include other pulse scenarios. For example, the user may be tasked with locating another pulse site, such as one or more of the temporal, carotid, apical, brachial, radial, femoral, popliteal, posterior tibial, dosalis pedis, or the like arterial sites. The simulation system **100** may also inform the user of additional information and/or pose a second task to the user. In one version, after the user has adequately located the correct position on the wrist to take a pulse, the user may be informed: “An alternative place to take the pulse is just in front of the ear, where the temporal artery passes to the forehead” and then the user may be tasked to locate this position on the graphical representation **120** which may then be in the form of the head of a patient. Alternatively, the graphical representation **120** may be in the form of a full body during both scenarios.

In more advanced training routines, the trainee may be taught to evaluate the detected pulse. For example, the simulation system **100** may instruct the user that: “If no pulse can be detected from extreme locations such as the wrist or the temporal artery, the patient may have collapsed from shock or undergone cardiac arrest. The only place that a pulse can then be felt is over the carotid artery where it passes up the neck next to the Adam's apple.” The simulation system **100** may then task the user with finding this location and/or may task the user

to make diagnostic determinations based on the relative strengths of the pulse at multiple locations. In another version, the user may be tasked with evaluating the detected pulse at a particular site. For example, the user may be presented various pulse rates and tasked with determining the pulse rate. The simulation system 100 may display a simulated watch 170 or other timer, as shown in Figure 3, to allow the user to practice counting the number of beats for 15 seconds, a minute, or for another period of time. Alternatively or in a different mode, no timer may be shown in order to allow the trainee to acquire an intuitive knowledge of an approximate pulse rate. Various pulse rates and/or pulse strengths may be presented to the user and the user may be asked to estimate the pulse rate to allow the user to gain this fundamental and intuitive knowledge. For more advanced trainees, the haptic sensation may, for example, simulate tachycardia, bradycardia, thrill or other vascular related conditions and the user may be tasked with accurately detecting the presented condition. In another version, different species of animals may be graphically represented, and the trainee may be tasked with locating one or more pulse taking locations for each displayed animal. For example, a veterinary student or trainee may be presented with a series of pulse taking scenarios related to a dog, a cat, a bird, etc. In any of the above scenarios, other graphical images and/or audible signals may be provided. For example, the graphical environment 110 may comprise an image of a stethoscope to instruct the user how to properly position the stethoscope to listen to blood flow and/or breathing sounds. The simulation system 100 coordinates the audible, visual, and/or haptic outputs provided to the user.

The cursor 115 displayed to the user and representative of the user in the graphical environment 110 may appear as an extension of the user. For example, the cursor 115 may resemble the body part of the user that would be used by the user during an actual palpation procedure. In the version shown in Figure 3 where the simulation system 100 comprises a pulse trainer, the cursor 115 takes the form of one or more fingers 175, such as the first and second fingers of the right hand, to create a more authentic virtual reality environment to the user. Alternatively, the orientation of the fingers may be altered and/or more or less of the body part may be displayed. Additionally, the orientation of the cursor 115 may be adjustable when using a user object 130 with a sensed rotational degree of freedom, such as when using an instrument glove or the like, or through keyboard instruction or the like.

In another particular example of the simulation system 100, the simulation system 100 may comprise a palpation trainer adapted to train a user to properly locate and/or

evaluate a feature under the surface of a living body or on or near the surface of a living body. Medical practitioners often touch and feel at least a portion of a patient's body with his or her hands to examine the size, consistency, texture, location, or tenderness of an organ or body part. For example, a palpation procedure may be used to: 1) locate an anatomical feature below the surface of the skin, such as a blood vessel during a vascular access procedure; 2) locate an internal organ, such as a liver, for anatomical or diagnostic purposes and/or evaluate an internal organ, such as by evaluating the size, resiliency or tenderness of a liver, to make at least a preliminary determination of the condition of the internal organ or the patient; 3) locate hard tissue, such as a bone or cartilage, in the body and/or examine a condition of the hard tissue, such as making a preliminary fracture evaluation or detecting calcification of bony tissue; 4) test the strength of tendons and/or ligaments of the body, such as testing the condition of the ligaments of a knee by examining the amount of side to side play that exists between the tibia and the femur; 5) locate and examine lymph nodes to detect abnormal conditions thereof; 6) examine tissues, such as a breast or a testicle, for the presence of a cellular mass and/or a tumor that might be indicative of a disease state that warrants further investigation; 6) locate foreign objects in the body; and/or 7) otherwise locate soft or hard tissue for the purpose of evaluating, treating, caring for, or administering to the tissue, such as by providing therapeutic massage. A version of a graphical environment 110 associated with a version of a palpation trainer is shown in Figure 4. In this version, an entire hand 180 may be displayed as the cursor 115 to provide a realistic simulation of the procedure. Though a left hand is shown, either hand (or both hands) may be displayed and controlled by the user object 130.

The simulation system 100 comprising a palpation trainer may present feature location and/or evaluation scenarios to the trainee. For example, a version of an abdominal evaluation trainer will now be described for the purpose of illustrating concepts of the invention. The training session may comprise one or more of the following interactive graphical environments or situations.

The simulation system 100 may begin by displaying a graphical representation 120 representing the abdominal region 185 of a patient, the cursor 115 may or may not be displayed during this portion of the training. The simulation system 100 may then inform the user either visually or audibly that: "An evaluation of the abdominal region may begin with inspection. Look at the abdomen and the abdominal contour and note any asymmetry, the location of scars, rashes, or other lesions." The simulation system 100 may present asymmetry

and/or scar, rash, or lesion scenarios to the user and may provide a location for the recordation of such by the user.

Next, the user may be informed: “Normally, auscultation occurs after a complete palpation procedure. However, when evaluating the abdomen, it is often desirable to perform auscultation before palpation due to the possibility of altering conditions during the palpation process. Begin by recording bowel sounds as being present, increased, decreased, or absent.” At this time, the simulation system **100** may generate a graphical object representing a stethoscope (not shown in Figure 4) to allow the user to simulate auscultation. According to program code, the sounds may either be normal or may indicate an abnormal condition. The simulation system **100** may allow the user to sample various sounds or may present only a single sound to the user in order to test or evaluate the user. The simulation may continue by informing the user: “In addition to bowel sounds, abdominal bruits are sometimes heard. Listen over the aorta, renal, and iliac arteries.” Scenarios related to bruits may then be presented. The user may be tasked to determine which bruits are representative of diseased states and which are not, for example bruits confined to systole do not necessarily indicate disease. More advanced training systems may task the user to determine, for example, the difference between a bruit and a heart murmur transmitted to the abdominal region.

The user may then be tasked with performing percussion on the abdomen. For example, the user may be provided information relevant to an examination, such as: “With the patient in a supine position, perform percussion on the patient. A tympanic sensation will be present over most of the abdomen in a healthy individual. However, a dullness may be a clue to an underlying abdominal mass.” The graphical representation **120** may then be shown as though the patient were in a supine position. The user may then be tasked to position the cursor **115**, such as the graphical image of a hand **180**, over portions of the abdomen on which percussion is to be performed. When the cursor is correctly positioned, a haptic sensation may be provided to the user. Alternatively or additionally, continuous haptic sensations indicative of the contour of the abdomen (or other body part in other procedures) may be provided so that the user is provided with kinesthetic force feedback of the feel of the graphical image **120**.

Percussion, which is normally performed by using a second hand to strike a finger in contact with the patient may then be simulated. In a simple form, the percussion may be simulated by depression of a digital or analog button on the user object **130**. This will cause the graphical environment **110** to display another hand performing a percussion on the cursor **115** hand. The

vibrations resulting from the simulated percussion may then be applied to the user haptically through the user object **130**. In this way, the user will be able to detect the difference between the tympanic sensation and the dull sensation. Various percussion scenarios may be presented, for example, the user may be tasked with: “Measure the liver span by percussing hepatic

5 dullness from near the lungs and from near the bowel. A normal liver span is 6 to 12 cm in the midclavicular line.” A user may then learn to make a liver size determination. Continuing, the simulation system **100** may inform the user: “To detect an enlarged spleen, percuss the lowest interspace in the left anterior axillary line. After the patient takes a deep breath, a change in the sensation from a tympany to a dull signal may suggest an enlarged spleen.” The user then

10 locates the correct positions for the percussion, at which time a haptic sensation may be provided, and the user then makes diagnostic determinations based on the haptic sensations applied to the user.

The user may then be instructed how to properly examine the region using the sense of touch. For example, the simulation system **100** may inform the user: “After

15 percussion, begin with light palpation on the surface of the body and watch the patient for areas of tenderness. The most sensitive indicator of tenderness is the patient's facial expression. Voluntary or involuntary guarding of a region may also be present.” The simulation system **100** may display a graphic representation of the face selectively showing, in various degrees,

20 discomfort or may audibly simulate sounds of discomfort coming from the patient. Haptic feedback during the portion of the training may include surface contour indications either via tactile sensations or kinesthetic force sensations. Next, the user is instructed: “Proceed to deep palpation. Pressing gently but deeply into the abdomen, identify abdominal masses and areas of deep tenderness.” The user then simulates a deep palpation technique, and haptic sensations

25 indicative of deeply felt features are fed back to the user. In one version, tactile sensations or lateral forces indicate to the user the presence of internal features. In another version, the user object **130** is manipulatable in three dimensions and a force may be applied to the user object **130** that simulates the force experienced when pressing into the patient. In another version, a force sensor may be provided on the user object that detects the force applied by the user to

30 control the display of the cursor **115** in relation to the graphical representation **120** so that the user has to apply a force in order to deeply palpate the patient. Haptic effects may be provided during the application of the force to simulate the presence of deep features.

During the deep palpation, organs may be located and evaluated. For example, the user may be informed: "Palpate the edge of the liver. Place your fingers just below the costal margin and press firmly. As the patient takes a deep breath, you may feel the edge of the liver press against or slide under your hand. A normal liver is not tender." The simulation system 100 may provide to the user a haptic sensation indicating that the liver and/or the liver edge has been properly located. The user may then simulate the asking of the patient to take a deep breath, for example by pressing a button or the like, after which a haptic sensation simulating the movement of the liver may be applied to the user. The simulation may then continue to task the user to find other organs. For example: "Try to feel the spleen. Press down just below the left costal margin with your right hand while asking the patient to take a deep breath. If necessary, use your left hand to lift the lower rib cage and flank. A palpable spleen may be indicative of a diseased condition." The user may then be presented with a spleen haptic sensation indicating, for example, an inflamed or ruptured spleen.

The above training process may be altered. For example, in each of the described graphical environments 110, the location of a feature may or may not be visually displayed. For example, a feature, such as a liver, may be shown in phantom, or may be shown when a user graphically selects a button causing the feature to be shown. Alternatively to the instruction process described above, one or more scenarios may be provided to the user without the instructional information. This version may be used to test or evaluate a user's ability level. Also, other palpation procedures may be similarly simulated using the simulation system 100. For example, the simulation system 100 may instruct a user on how to properly locate a vein in the arm, how to properly evaluate chest vibrations during breathing or talking, how to assess trauma by feeling a joint, how to beneficially and non-traumatically give a therapeutic massage to a portion of the body, etc.

In addition to being useful in training medical practitioners, a palpation trainer is also useful in teaching a patient to treat and/or evaluate themselves. For example, a breast tumor locating simulation procedure may be used to teach a woman or her partner how to properly examine the woman's breasts for abnormalities. Additionally, a patient with a fistula or a graft may use a palpation trainer to learn how to properly feel for a vibration related to a vascular thrill. Lack of thrill can be indicative of a clot in the access and should be checked by the patient on a daily basis. The palpation trainer may be used to teach the patient how the

blood flow condition should feel and present scenarios that should indicate to the user that a physician should be contacted.

The haptic interface device **140** may be designed to provide authentic haptic interaction between the user and the graphical environment **110**. In a relatively simple version, the user object **130** may be, for example, a one degree of freedom interface device, such as a rotatable knob or a linearly insertable elongated member. In another version, the user object **130** is moveable in at least two linear degrees of freedom. In more complex versions, the user object may be movable in three dimensions. For example, the haptic interface device **140** may comprise a three to six degree of freedom interface device such as those described in U.S. Patents 5,701,140 and 5,828,197 which are available from Immersion Corporation in San Jose, California, both of which are incorporated herein by reference in their entireties, and in U.S. Patent 5,625,576 which is incorporated herein by reference in its entirety. By providing these additional actuatable degrees of freedom, kinesthetic forces can be applied in three dimensions to provide an authentic virtual reality experience to the user of the simulating system **100**. An even more advanced simulation system **100** may comprise a graphical hand controller that is capable of not only positioning the cursor **115** comprising a hand **180**, but is also capable of controlling the position of one or more of the fingers on the hand, such as by using a Cyberglove™, Cybergrasp™ or Cyberforce™ device described in U.S. Patents 5,631,861 and 6,042,555 which are available from Virtual Technologies, Inc. of Palo Alto, California, both patents being incorporated herein by reference in their entireties.

In a particular version of the simulation system **100**, the haptic interface device **140** comprises a mouse **200** which is manipulatable in a planar workspace **205** by a user, as shown for example in Figure 5. This version is convenient and inexpensive to implement while still providing an advantageous haptic feedback experience to the user. U.S. Patents 6,211,861, 6,100,874, 6,166,723, U.S. Patent Application Serial No. 09/585,741 filed on June 2, 2000, and U.S. Provisional Patent Application 60/224,584 filed on October 11, 2000 describe versions of haptic mice and are incorporated herein by reference in their entireties.

Figure 5 is a perspective view schematically illustrating a version of a simulation system **100** of the present invention where the controller **125** is implemented in a computer **210** and the haptic interface device **140** comprises a mouse **200**. Either the entire mouse **200** may serve as the actuatable user object **130** or the housing **215** of the mouse **200** may serve as the

actuatable user object **130**. As the mouse **200** is manipulated by a user, its position is detected and the manipulation is communicated to the computer **210** to, for example, control the positioning of the cursor **115** on a computer screen **220**. Mouse **200** is an object that is engaged and manipulated by a user. In the described embodiment, mouse **200** is shaped so that a user's
 5 fingers or hand may comfortably grasp the object and move it in the provided degrees of freedom in physical space. For example, a user can move mouse **200** to provide planar two-dimensional input to a computer system to correspondingly move a cursor **115**, such as an arrow cursor, a cursor representing a portion of a user as discussed above, or a virtual character, vehicle, or other entity in a game or simulation, in a graphical environment **110** provided by
 10 computer **210**. In addition, mouse **200** may include one or more buttons **225a** and **225b** to allow the user to provide additional commands to the computer **210**. The mouse **200** may also include additional buttons. For example, a thumb button can be included on one side of the housing **215** of mouse **200**. Typically, the mouse **200** is a smooth- or angular-shaped compact unit that is designed to fit under a user's hand, fingers, and/or palm, but can also be
 15 implemented as a grip, finger cradle, cylinder, sphere, planar object, etc.

In the version shown in Figure 5, the computer **210** may comprise a processor and may be capable of executing program code. For example, the computer **210** may be a personal computer or workstation, such as a PC compatible computer or Macintosh personal
 20 computer, or a Sun or Silicon Graphics workstation. The computer **210** may be operable under the Windows™, MacOS, Unix, or MS-DOS operating system or similar. Alternatively, the computer **210** can be one of a variety of home video game console systems commonly connected to a television set or other display, such as systems available from Nintendo, Sega, or Sony. In other embodiments, the computer **210** can be a "set top box" which can be used, for
 25 example, to provide interactive television functions to users, or a "network-" or "internet-computer" which allows users to interact with a local or global network using standard connections and protocols such as used for the Internet and World Wide Web. The computer **210** may include a host microprocessor, random access memory (RAM), read only memory (ROM), input/output (I/O) circuitry, and/or other components of computers well-known to those
 30 skilled in the art. Computer **210** may implement an application program with which a user is interacting via peripherals, such as mouse **200**. For example, the application program can be a simulation program, such as a medical procedure simulation program. Alternatively, the application program may be a computer aided design or other graphic design program, an operating system, a video game, a word processor or spreadsheet, a Web page or browser that

implements, for example, HTML or VRML instructions, a scientific analysis program, or other application program that may or may not utilize haptic feedback. Herein, for simplicity, operating systems such as Windows™, MS-DOS, MacOS, Linux, Be, etc. are also referred to as “application programs.” The application program may comprise an interactive graphical

5 environment, such as a graphical user interface (GUI) to allow the user to input information to the program. Typically, the application provides images to be displayed on a display **220** and/or outputs other feedback, such as auditory signals. The computer **210** is capable of generating a graphical environment **110**, which can be a graphical user interface, game, simulation, such as those described above, or other visual environment. The computer displays graphical objects,

10 such as graphical representations and graphical images, or “computer objects,” which are not physical objects, but are logical software unit collections of data and/or procedures that may be displayed as images by computer **210** on display screen **220**, as is well known to those skilled in the art. The application program checks for input signals received from the electronics and sensors of mouse **200**, and outputs force values and/or commands to be converted into haptic

15 output for mouse **200**. Suitable software drivers which interface such simulation software with computer input/output (I/O) devices are available from Immersion Corporation of San Jose, California. Display screen **220** can be included in the computer **210** and can be a standard display screen (LCD, CRT, flat panel, etc.), 3-D goggles, or any other visual output device. Typically, the host application provides images to be displayed on display device **220** and/or

20 other feedback, such as auditory signals.

In the version of Figure 5, the mouse **200** rests on a ground surface **205** such as a tabletop, mousepad, or a platform. A user grasps the mouse **200** and moves the mouse **200** in a planar workspace on the surface **205** as indicated by arrows **230**. Mouse **200** may be moved

25 relative to the ground surface **205**, and in one version may be picked up and placed in a different location. In another version, the mouse **200** is linked to the ground surface **205**. A frictional ball and roller assembly (not shown) can in some embodiments be provided on the underside of the mouse **200** to translate the planar motion of the mouse **200** into electrical position signals, which are sent to the computer **210** over a bus **235** as is well known to those skilled in the art.

30 In other embodiments, different mechanisms and/or electronics can be used to convert mouse motion to position or motion signals received by the computer **210**, as described below. Mouse **200** may be a relative device, in which its sensor detect a change in position of the mouse, allowing the mouse **200** to be moved over any surface at any location. Alternatively, an absolute mouse may also be used, in which the absolute position of the mouse **200** is known

with reference to a particular predefined workspace. The bus **235**, which communicates signals between mouse **200** and computer **210** may also provide power to the mouse **200**. Components such as actuator **135** may require power that can be supplied from a conventional serial port or through an interface such as a USB or Firewire bus. In other embodiments, signals can be sent between mouse **200** and computer **210** by wireless transmission/reception. In some embodiments, the power for the actuator can be supplemented or solely supplied by a power storage device provided on the mouse **200**, such as a capacitor or one or more batteries. Some embodiments of such are disclosed in U.S. Patent No. 5,691,898, which is incorporated herein by reference in its entirety.

Mouse **200** may include or be acted on by an actuator **135** which is operative to produce forces on the mouse **200** and thereby provide haptic sensations to the user. The mouse **200** may be either a tactile mouse or a kinesthetic force feedback mouse, or both. In one version a tactile mouse comprises, for example, an actuator **135** positioned within the mouse **200** and outputs a force to the housing **215** of the mouse **200**. This version is particularly useful in providing tactile sensations, such as vibrations, to the user. In one version, the actuator **135** comprises a grounded link that is connected to the mouse **200** to provide kinesthetic force feedback to the mouse **200** in two or more degrees of freedom, for example by forcing the mouse **200** in the direction of arrows **230**. This version is particularly useful in kinesthetically simulating contours and the feel of objects. Each of these versions will be described herein below.

Figure 6 is a side cross-sectional view of a version of the mouse **200** of Figure 5 where the mouse is a tactile mouse **250**. Tactile mouse **250** includes one or more actuators **135** for imparting haptic feedback such as tactile sensations to the user of the tactile mouse **250**. The actuator **135** outputs forces on the tactile mouse **250** which the user is able to feel. The embodiment of Fig. 6 is intended to provide inertial forces rather than contact forces; contact forces are described with respect to Fig. 7. In some embodiments, two or more actuators **135** can provide inertial forces or contact forces, or one actuator **135** can provide inertial forces, while a different actuator **135** can provide contact forces.

Tactile mouse **250** includes a housing **215**, a sensing system **255**, and a tactile actuator assembly **260**. Housing **215** is shaped to fit the user's hand like a standard mouse while the user moves the tactile mouse **250** in the planar degrees of freedom and manipulates

the buttons **225a**, **225b**. Other housing shapes can be provided in many different embodiments.

Sensing system **255** detects the position of the tactile mouse **250** in its planar degrees of freedom, e.g. along the X and Y axes. In the described embodiment, sensing system **255** includes any one of known sensing technologies. For example, in the version shown, a standard mouse ball **265** for providing directional input to the computer **210**. Ball **265** is a sphere that extends partially out the bottom surface of the tactile mouse **250** and rolls in a direction corresponding to the motion of the tactile mouse **250** on a planar surface **205**. For example, when the tactile mouse **250** is moved in a direction indicated by arrow **270** (y direction), the ball rotates in place in a direction shown by arrow **275**. The ball motion can be tracked by a cylindrical roller **280**, or the like, which is coupled to a sensor **285** for detecting the motion of the mouse. A similar roller and sensor can be used for the x-direction which is perpendicular to the y-axis. Other types of mechanisms and/or electronics for detecting planar motion of the tactile mouse **250** can be used in other embodiments. In some embodiments, high frequency tactile sensations can be applied by the actuator that cause a mouse ball **265** to slip with respect to the frictionally engaged rollers. In another version, an optical sensor that has no moving mouse ball component may be used. A suitable optical mouse technology is made by Agilent of Palo Alto, CA and can be advantageously combined with the tactile sensation technologies described herein, where the optical sensor detects motion of the mouse relative to the planar support surface by optically taking and storing a number of images of the surface and comparing those images over time to determine if the mouse has moved. For example, the IFeel™ mouse device from Logitech Corporation uses this type of sensor.

Buttons **225a**, **225b** can be selected by the user as a “command gesture” when the user wishes to input a command signal to the computer **210**. The user pushes a button **225a**, **225b** down (in the degree of freedom of the button approximately along axis z) to provide a command to the computer **210**. The command signal, when received by the computer **210**, can manipulate the graphical environment in a variety of ways. In one embodiment, an electrical lead can be made to contact a sensing lead as with any mechanical switch to determine a simple on or off state of the button. An optical switch or other type of digital sensor can alternatively be provided to detect a button press. In a different continuous-range button embodiment, a sensor can be used to detect the precise position of one or more of the buttons **225a**, **225b** in its range of motion (degree of freedom). In some embodiments, one or more of the buttons **225a**, **225b** can be provided with force feedback (instead of or in addition to the tactile feedback from

actuator 135), as described in copending U.S. Patent Application Serial No. 09/235,132, filed on February 18, 1999 and which is incorporated herein by reference in its entirety.

The tactile actuator assembly 260 may include an actuator assembly 54, and the actuator assembly includes an actuating mechanism 290, such as a motor, a flexure mechanism (“flexure”) 295, and an inertial mass 300 coupled to the actuating mechanism 290 by the flexure 295. The inertial mass 300 is moved in a linear direction by the actuating mechanism 290, for example approximately in the z-axis 305 which is approximately perpendicular the planar workspace of the mouse 200 in the x- and y-axes, e.g. the mouse’s position or motion is sensed in the x-y plane. The tactile actuator 260 is coupled to the housing 215 of the tactile mouse 250 such that inertial forces caused by the motion of the inertial mass 300 are applied to the housing 215 of the tactile mouse 250 with respect to the inertial mass, thereby conveying haptic feedback such as tactile sensations to the user of the tactile mouse 250 who is contacting the housing 215. Thus, the actuating mechanism 290 need not directly output forces to the user or to a user-manipulatable object, but instead the moving mass creates an inertial force that is indirectly transmitted to the user. Thus, the inertial mass is used as a grounding reference for tactile sensations. Alternatively, the actuating mechanism 290 may directly apply the forces or may be coupled to a rotating eccentric mass.

The version shown in Figure 6 provides inertial forces that are directed substantially in a single particular degree of freedom, i.e. along a particular axis. In most embodiments, crisp haptic sensations cannot typically be achieved using a continuously rotating eccentric mass, which provides an undirected inertial force in a rotating plane and creates a generalized wobble on the device. Therefore, a linear inertial force is desirable. It is important to consider the direction or degree of freedom that the linear force is applied on the housing of the mouse device with respect to the inertial mass. If a significant component of the force is applied along one or more of the moveable planar degrees of freedom of the mouse (i.e., the x or y axis) with respect to the inertial mass, the short pulse can jar the mouse in one or both of those planar degrees of freedom and thereby impair the user’s ability to accurately guide a controlled graphical object, such as a cursor, to a given target. Since a primary function of a mouse is accurate targeting, a tactile sensation that distorts or impairs targeting, even mildly, is usually undesirable. To solve this problem, the mouse device of the present invention applies inertial forces substantially along the z axis, orthogonal to the planar x and y axes of the mouse controller. In such a novel configuration, tactile sensations can be applied at a perceptually

strong level for the user without impairing the ability to accurately position a user controlled graphical object in the x and y axes. Furthermore, since the tactile sensations are directed in a third degree of freedom relative to the two-dimensional mouse planar workspace and display screen, jolts or pulses output along the z axis feel much more like three-dimensional bumps or divots to the user, increasing the realism of the tactile sensations and creating a more compelling interaction. For example, an upwardly-directed pulse that is output when the cursor is moved over a window border creates the illusion that the mouse is moving “over” a bump at the window border.

One version of the tactile mouse **250** provides linear output forces using a rotary actuator, i.e. an actuator outputting a rotary force (torque). In the current actuator market, rotary actuators such as rotary DC motors are among the most inexpensive types of actuators that still allow high bandwidth operation (when driven with signals through, for example, an H-bridge type amplifier). These types of motors can also be made very small and output high magnitude forces for their size. Thus, actuating mechanism **290** may be a DC motor, but can be other types of rotary actuators in other embodiments. For example, a moving magnet actuator can be used instead of a DC motor; such an actuator is described in detail in copending patent application no. 60/133,208, incorporated herein by reference. Other types of actuators can also be used, such as a stepper motor controlled with pulse width modulation of an applied voltage, a pneumatic/hydraulic actuator, a torquer (motor with limited angular range), shape memory alloy material (wire, plate, etc.), a piezo-electric actuator, etc. The tactile mouse **250** in the version shown in Figure 6 makes use of low cost flexure as a mechanical transmission to convert a rotary actuator force to a linear force that is used to move the inertial mass, and to also amplify the forces to allow more compelling haptic sensations. Versions of the flexure are described in U.S. Patent Application 09/585,741. In the described embodiment of Figure 6, tactile actuator **260** has a stationary portion which is coupled to a part of the housing **215** (and thus stationary only with respect to the portion of the mouse housing to which it is coupled), for example by being coupled to bottom portion **310** of the housing **215**. A rotating shaft of the actuating mechanism **290** is coupled to the moving portion of the assembly that includes the inertial mass **300** and at least part of the flexure **295**, where the inertial mass moves linearly approximately along the Z-axis. The actuating mechanism **290** is operative to oscillate the inertial mass **300** (or itself in some embodiments) quickly along an axis which is approximately parallel to the Z axis. Thus, forces produced by the oscillation of the inertial mass **300** are transmitted to the housing **215** through the tactile actuator **260** and felt by the user.

Alternatively, directed inertial forces can be output along the X and Y axes in the planar workspace of the device and can be compensated for to prevent or reduce interference with the user's control of the device. One method to compensate is to actively filter imparted jitter in that workspace, as disclosed in U.S. Patent No. 6,020,876 which is incorporated herein
 5 by reference in its entirety. The x and y directed tactile sensations may also provide advantageous and authentic palpation related tactile sensations.

One way to direct an inertial force is to directly output a linear force, e.g., a
 10 linear moving voice coil actuator or a linear moving-magnet actuator can be used, which are suitable for high bandwidth actuation. These embodiments are described in greater detail in U.S. Patent No. 6,211,861 which is incorporated herein by reference in its entirety. These embodiments allow for high fidelity control of force sensations in both the frequency and magnitude domains, and also allow the forces to be directed along a desired axis and allows for
 15 crisp tactile sensations that can be independently modulated in magnitude and frequency.

Figure 7 is a side elevational view of another version of a tactile mouse **250'**. In this version, the linear motion provided by the tactile actuator **260** is used to drive a portion of the housing **215** (or other member) that is in direct contact with the user's hand (finger, palm, etc.). The tactile actuator **260** of this version includes an actuating mechanism **290**, flexure **295**,
 20 and inertial mass similar to the version of Figure 6 (except that the actuating mechanism and flexure of Fig. 7 are shown rotated approximately 90 degrees with respect to Fig. 6). The tactile mouse **250'** of Figure 7 includes a moving cover portion **320** which can be part of the housing **215**. Cover portion **320** is coupled to the rest of the housing **215** by a hinge allowing their
 25 respective motion, such as a mechanical hinge, a flexure, rubber bellows, or other type of hinge. Cover portion **320** may thus rotate about an axis B of the hinge. In other embodiments, the hinge can allow linear or sliding motion rather than rotary motion between cover and housing portions. In the embodiment shown, the cover portion **320** extends in the y-direction from about the mid-point of the mouse housing to near the back end of the tactile mouse **250'**. In other
 30 embodiments, the cover portion **320** can cover larger or smaller areas. Various embodiments of such a moveable cover portion are described in copending patent application no. 09/253,132. The cover portion **320** is rotatably coupled to a link **325**, and the link **325** is rotatably coupled at its other end to the linear moving portion the flexure **295**. Thus, as the member of the flexure **295** is moved along the z-axis, this motion is transmitted to the cover portion **320** through the

link **325**, where the rotational couplings of the link allow the cover portion **320** to move about axis B of the hinge. The actuating mechanism **290** can drive the flexure **295** up on the z-axis, which causes the cover portion **320** to move up to, for example, the dashed position shown.

5 The user feels the force of the cover portion **320** against his or her hand (such as the palm) as a contact force (as opposed to an inertial force). When the cover portion is oscillated, the user can feel a vibration-like force. The cover portion can also be used to designate 3-D elevations in a graphical environment. In some embodiments, the configuration described can inherently provide an inertial force as well as the contact force if an inertial mass
10 is moved as described above in addition to the contact portion. In other embodiments, a different "contact member" (e.g. a member that is physically contacted by the user) can be moved instead of the cover portion **320** but in a similar fashion, such as mouse buttons **225a**, **225b** or other buttons, tabs, mouse wheels, or dials. Furthermore, in some embodiments multiple actuator assemblies can be used to drive a cover portion and one or more buttons or
15 other controls of the tactile mouse **250'**. Furthermore, in some embodiments, one actuator assembly can be used to move a cover portion **320** or other member, and a different actuator assembly can be used to provide an inertial force as in the embodiment of Figure 6, where the inertial and contact forces can operate in conjunction if desired.

20 Figure 8 is a side elevational view of another version of a tactile mouse **250''** including another embodiment of the tactile actuator **260** of the present invention. In this version, the actuating mechanism also acts as the inertial mass or moving element. As shown in Figure 8, the tactile actuator **260** can be positioned on the bottom portion **310** of the mouse housing **215**, where space **330** is allowed for the tactile actuator **290** to move along the z-axis
25 without impacting the housing **215** as described in U.S. Patent Application Serial No. 09/585,741. In other embodiments, the tactile actuator **260** can be positioned on other surfaces in the housing, such as the top or sides.

30 Providing the actuating mechanism **290** as the inertial mass that is driven in the z-axis has several advantages. For example, this embodiment saves the cost of providing a separate inertial mass and saves space and total weight in the device. Another advantage of this version is that it has a very low profile in the z-axis dimension. This is allowed by the orientation of the actuating mechanism **290** in the x-y plane, e.g. the axis of rotation of the actuator shaft is parallel to the z-axis.

Figure 9 is a block diagram illustrating one embodiment of the simulation system 100 where the controller 125 may comprise a computer 210 and the haptic interface device 140 may comprise a tactile mouse 250, such as one of the tactile mice discussed above. In this version, the tactile mouse 250 comprises a local microprocessor 350. However, the invention may be implemented with higher level control.

The computer 210 may include a processor 355, such as a microprocessor, a clock 360, a display screen 220, and an audio output device 365. The computer 210 may also include other well known components, such as random access memory (RAM), read-only memory (ROM), and input/output (I/O) electronics (not shown). Display screen 220 displays images of a simulation, game environment, operating system application, etc. Audio output device 365, such as speakers, is preferably coupled to host microprocessor 355 via amplifiers, filters, and other circuitry well known to those skilled in the art and provides sound output to user when an "audio event" occurs during the implementation of an application program. Other types of peripherals can also be coupled to host processor 355, such as storage devices (hard disk drive, CD ROM drive, floppy disk drive, etc.), printers, and other input and output devices.

The haptic interface device 140, such as a tactile mouse 250, is coupled to the computer 210 by a bi-directional bus 235. The bi-directional bus 235 sends signals in either direction between the computer 210 and the interface device 140. Bus 235 can be a serial interface bus, such as an RS232 serial interface, RS-422, Universal Serial Bus (USB), MIDI, or other protocols well known to those skilled in the art, or a parallel bus or wireless link. For example, the USB standard provides a relatively high speed interface that can also provide power to the actuator 135.

The haptic interface device 140, such as the tactile mouse 250 can include a local controller, such as a local microprocessor 350. Local microprocessor 350 can optionally be included within the housing 215 of the tactile mouse 250 to allow efficient communication with other components of the tactile mouse 250. By local it is meant that the processor 350 is a separate processor from any processors in the computer 210. The local microprocessor 350 may be dedicated to haptic feedback and sensor I/O of the tactile mouse 250. Local microprocessor 350 can be provided with software instructions to wait for commands or requests from the computer 210, decode the command or request, and handle/control input and output signals

according to the command or request. In addition, local processor **350** can operate independently of the computer **210** by reading sensor signals and calculating appropriate forces from those sensor signals, time signals, and stored or relayed instructions selected in accordance with a host command. Suitable microprocessors for use as local microprocessor **350** include the
5 MC68HC711E9 by Motorola, the PIC16C74 by Microchip, and the 82930AX by Intel Corp., for example, as well as more sophisticated force feedback processors such as the Immersion Touchsense Processor, available from Immersion Corporation in San Jose, California. Local microprocessor **350** can include one microprocessor chip, multiple processors and/or co-processor chips, and/or digital signal processor (DSP) capability.

10
Local microprocessor **350** can receive signals from sensor(s) **370** and provide signals to tactile actuator **260** in accordance with instructions provided by the computer **210** over bus **235**. For example, in a local control embodiment, the computer **210** provides high level supervisory commands to local microprocessor **350** over bus **235**, and local
15 microprocessor **350** decodes the commands and manages low level force control loops to sensors **370** and the tactile actuator **260** in accordance with the high level commands and independently of the computer **210**. This operation is described in greater detail in US Patents 5,739,811 and 5,734,373, both incorporated by reference herein in their entireties. In the computer control loop, force commands are output from the computer **210** to local
20 microprocessor **350** and instruct the local microprocessor **210** to output a force or force sensation having specified characteristics. The local microprocessor **350** reports data to the computer **210**, such as locative data that describes the position of the tactile mouse **250** in one or more provided degrees of freedom. The data can also describe the states of buttons **225a**, **225b** and a safety switch **375**. The computer **210** uses the data to update executed programs. In the
25 local control loop, actuator signals are provided from the microprocessor **350** to tactile actuator **260** and sensor signals are provided from the sensor **370** and other input devices **380** to the local microprocessor **350**. Herein, the term “haptic sensation” or “tactile sensation” refers to either a single force or a sequence of forces output by the tactile actuator **260** which provide a sensation to the user. For example, vibrations, a single jolt or pulse, or a texture sensation are all
30 considered haptic or tactile sensations. The local microprocessor **350** can process inputted sensor signals to determine appropriate output actuator signals by following stored instructions. The microprocessor **350** may use sensor signals in the local determination of forces to be output on the housing **215**, as well as reporting locative data derived from the sensor signals to the host computer.

In yet other embodiments, other simpler hardware can be provided locally to tactile mouse **250** to provide functionality similar to microprocessor **350**. For example, a hardware state machine incorporating fixed logic can be used to provide signals to the tactile actuator **260** and receive sensor signals from sensors **370**, and to output tactile signals according to a predefined sequence, algorithm, or process. Techniques for implementing logic with desired functions in hardware are well known to those skilled in the art.

In a different, host-controlled embodiment, the computer **210** can provide low-level force commands over bus **235**, which are directly transmitted to the tactile actuator **260** via local microprocessor **350** or other (e.g. simpler) circuitry. The computer **210** thus directly controls and processes all signals to and from the tactile mouse **250**, e.g. the computer **210** directly controls the forces output by tactile actuator **260** and directly receives sensor signals from sensor **370** and input devices **380**. This embodiment may be desirable to reduce the cost of the haptic feedback device yet further, since no local microprocessor **350** or other processing circuitry need be included in the tactile mouse **350**.

In the simplest host control embodiment, the signal from the host to the device can be a single bit that indicates whether to actuate the actuator at a predefined frequency and magnitude. In a more complex embodiment, the signal from the host could include a magnitude, giving the strength of the desired actuation. In yet a more complex embodiment, the signal can include a direction, giving both a magnitude and a sense for the actuation. In still a more complex embodiment, a local processor can be used to receive a simple command from the host that indicates a desired force value to apply over time. The microprocessor then outputs the force value for the specified time period based on the one command, thereby reducing the communication load that must pass between host and device. In an even more complex embodiment, a high-level command with tactile sensation parameters can be passed to the local processor **350** on the device which can then apply the full sensation independent of host intervention. Such an embodiment allows for the greatest reduction of communication load. Alternatively, a combination of numerous methods described above can be used for a single tactile mouse **250**.

Local memory **380**, such as RAM and/or ROM, is preferably coupled to microprocessor **350** in tactile mouse **250** to store instructions for microprocessor **350** and store

temporary and other data. For example, force profiles can be stored in memory **350**, such as a sequence of stored force values that can be output by the microprocessor, or a look-up table of force values to be output based on the current position of the tactile mouse **250**. In addition, a local clock **385** can be coupled to the microprocessor **350** to provide timing data, similar to the system clock of the computer **210**; the timing data might be required, for example, to compute forces output by tactile actuator **260** (e.g., forces dependent on calculated velocities or other time dependent factors). In embodiments using the USB communication interface, timing data for microprocessor **350** can be alternatively retrieved from the USB signal. For example, the computer **210** can send a “spatial representation” to the local microprocessor **350**, which is data describing the locations of some or all the graphical objects displayed in a GUI or other graphical environment which are associated with forces and the types/characteristics of these graphical objects. The microprocessor **350** can store such a spatial representation in local memory **380**, and thus will be able to determine interactions between the user object and graphical objects (such as the rigid surface) independently of the computer **210**. In addition, the microprocessor **350** can be provided with the necessary instructions or data to check sensor readings, determine cursor and target positions, and determine output forces independently of the computer **210**. The computer **210** could implement program functions (such as displaying images) when appropriate, and synchronization commands can be communicated between the microprocessor and the computer **210** to correlate the microprocessor and host processes. Also, the local memory **380** can store predetermined force sensations for the microprocessor that are to be associated with particular types of graphical objects. Alternatively, the computer **210** can directly send force feedback signals to the tactile mouse **250** to generate tactile sensations.

Sensors **370** sense the position or motion of the mouse (e.g. the housing **215**) in its planar degrees of freedom and provides signals to microprocessor **350** (or to computer **210**) including information representative of the position or motion. Sensors suitable for detecting planar motion of a tactile mouse include the sensing system **255** described above for Fig. 6, e.g. digital optical encoders frictionally coupled to a rotating ball or cylinder, as is well known to those skilled in the art. Optical sensor systems, linear optical encoders, potentiometers, optical sensors, velocity sensors, acceleration sensors, strain gauge, or other types of sensors can also be used, and either relative or absolute sensors can be provided. Optional sensor interface **390** can be used to convert sensor signals to signals that can be interpreted by the microprocessor **350** and/or computer **210**, as is well known to those skilled in the art.

Tactile actuator **260** transmits forces to the housing **215** of the tactile mouse **250** as described above with reference to Figures 6-8 in response to signals received from microprocessor **350** and/or computer **210**. Tactile actuator **260** is provided to generate inertial forces by moving an inertial mass, and/or contact forces by moving a contact member such as a cover portion **320**. The tactile actuator **260** has the ability to apply a short duration force on the housing **215** of the mouse with respect to an inertial mass. In one version, this short duration is directed substantially along a Z axis orthogonal to the X-Y plane of motion of the tactile mouse **250**. The short duration force may be a single burst of fixed magnitude and duration or may be controllable and/or shapeable. In one version, a periodic force can be applied to the housing of the tactile mouse **250** with respect to the inertial mass, where the periodic force can have a magnitude and a frequency, e.g. a sine wave; the periodic sensation can be selectable among a sine wave, square wave, saw-toothed-up wave, saw-toothed-down, and triangle wave; an envelope can be applied to the period signal, allowing for variation in magnitude over time; and the resulting force signal can be "impulse wave shaped" as described in U.S. Patent No. 5,959,613 which is incorporated herein by reference in its entirety. There are two ways the period sensations can be communicated from the host to the device. The wave forms can be "streamed" as described in U.S. Patent 5,959,613 and pending provisional patent application 60/160,401, both incorporated herein by reference in their entireties. Or the waveforms can be conveyed through high level commands that include parameters such as magnitude, frequency, and duration, as described in U.S. Patent 5,734,373 which is incorporated herein by reference in its entirety. These control schemes can also apply when providing contact forces using a moveable member. A short duration force command signal can also be used in those embodiments outputting both inertial and contact forces to move both the inertial mass and the contact member to provide simultaneous pulse sensations; or, the inertial mass can be controlled to output one sensation and the contact member can be simultaneously controlled to output a different sensation, such as a force of a different duration or magnitude, a vibration of a different frequency, a texture of a different spacing, etc.

Alternate embodiments can employ additional actuators for providing haptic sensations in the z-direction and/or in the degrees of freedom of the tactile mouse **250**. In one embodiment, the tactile mouse **250** can include multiple tactile actuators for greater magnitude forces, forces in multiple degrees of freedom, and/or different simultaneous haptic sensations. In another embodiment, the tactile mouse **250** can be enhanced with a secondary, different type of actuator in addition the actuator assembly described herein. Because of power constraints in

some embodiments, this secondary actuator can be passive (i.e., it dissipates energy). The passive actuator can be a brake, e.g., a brake employing a very low power substrate such as a magneto-rheological fluid. Alternatively, it can be a more traditional magnetic brake. The passive braking means can be employed through a frictional coupling between the mouse housing **215** and the table surface **205**. For example, a friction roller in the mouse housing base can engage the table surface. The roller can spin freely when the mouse is moved by the user so long as the passive brake is not engaged. When the brake is engaged, the user can feel the passive resistance to motion of the mouse (in one or two of the planar degrees of freedom of the mouse).

Actuator interface **395** can be optionally connected between tactile actuator **260** and local microprocessor **350** to convert signals from microprocessor **350** into signals appropriate to drive tactile actuator **260**. Actuator interface **395** can include power amplifiers, switches, digital to analog controllers (DACs), analog to digital controllers (ADCs), and other components, as is well known to those skilled in the art. It should be noted that circuitry should be provided to allow the actuator to be driven in two directions, since the preferred embodiment does not allow full revolutions of the actuator shaft, as described above. Circuitry for such bi-directional (harmonic) operation are well known to those skilled in the art and are also described in copending provisional patent application no. 60/142,155, incorporated herein by reference in its entirety.

Other input devices **380** may be included in the tactile mouse **250** and send input signals to microprocessor **350** or to the computer **210** when manipulated by the user. Such input devices include buttons **225a**, **225b** and can include additional buttons, dials, switches, scroll wheels, or other controls or mechanisms.

Power supply **397** can optionally be included in tactile mouse **250** coupled to actuator interface **395** and/or tactile actuator **260** to provide electrical power to the actuator, or may be provided as a separate component. Alternatively, and more preferably when possible, power can be drawn from a power supply separate from the tactile mouse **250**, or power can be received across a USB or other bus. Also, received power can be stored and regulated by tactile mouse **250** and thus used when needed to drive tactile actuator **260** or used in a supplementary fashion. Because of the limited power supply capabilities of USB, a power storage device may be required in the mouse device to ensure that peak forces can be applied (as described in U.S.

Patent No. 5,929,607, incorporated herein by reference in its entirety). For example, power can be stored over time in a capacitor or battery and then immediately dissipated to provide a jolt sensation to the mouse. Alternatively, this technology can be employed in a wireless mouse, in which case battery power is used to drive the tactile actuator **260**. In one embodiment, the battery can be charged by an electric generator on board the mouse, the generator driven by the user's motions of the mouse device. For example, a mouse ball or cylinder can turn a frictional roller or shaft that is coupled to and recharges the generator.

A safety switch **375** can optionally be included to allow a user to deactivate tactile actuator **260** for safety reasons. For example, the user must continually activate or close safety switch **375** during operation of tactile mouse **250** to enable the tactile actuator **250**. If, at any time, the safety switch is deactivated (opened), power from power supply **397** is cut to tactile actuator **260** (or the actuator is otherwise disabled) as long as the safety switch is needed. Embodiments include an optical switch, an electrostatic contact switch, a button or trigger, a hand weight safety switch, etc.

A basic tactile functionality desired for the tactile mouse **250** is a jolt sensation. A jolt sensation may be output when the cursor **115** is moved to a position where it intersects the graphical representation **120** or moved to a position where it lies within or near a predetermined region of the graphical representation **120**. The appropriate sensation for this simple cursor interaction is a quick, abrupt pop. This can be achieved by applying a crisp, short force between the inertial mass and the housing of the mouse device, e.g. by moving the inertial mass in one or a small number of oscillations. For example, a jolt can include a single impulse of force that quickly rises to a desired magnitude and then is turned off or quickly decays back to zero or small magnitude. The pulse can also or alternatively be output as a motion up and down of a contact member such as a cover portion of the housing of the mouse, in appropriate embodiments.

A vibration can also be output, which can include a series of jolts or pops applied periodically over a particular time period at a particular frequency. The time-varying force can be output according to a force vs. time waveform that is shaped like a sine wave, triangle wave, sawtooth wave, or other shape of wave. The vibration is caused by a mass or contact member oscillating back and forth.

In some embodiments, the sensation of a “spatial texture” may be output by correlating jolts and/or vibrations with the motion of the cursor over a graphical object or area. This type of force can depend on the position of the tactile mouse **215** in its planar workspace (or on the position of the cursor **115** in the graphical environment **110**). For example, the cursor **115** can be dragged over a graphical grating and jolts can be correlated with the spacing of the grating openings. Thus, texture bumps are output depending on whether the cursor **115** has moved over the location of a bump in a graphical object; when the mouse is positioned between “bumps” of the texture, no force is output, and when the mouse moves over a bump, a force is output. This can be achieved by host control (e.g., the host computer **210** sends the jolts as the cursor **115** is dragged over the grating) or by local control (e.g., the host computer **210** sends a high level command with texture parameters and the sensation is directly controlled by the tactile mouse **250** device). Some methods for providing texture sensations in a tactile sensation device are described in copending application no. 09/504,201, filed 2/15/00 and incorporated herein by reference in its entirety. In other cases, a texture can be performed by presenting a vibration to a user, the vibration being dependent upon the current velocity of the tactile mouse **250** in its planar workspace **205**. When the tactile mouse **250** is stationary, the vibration is deactivated; as the mouse moves faster, the frequency and magnitude of the vibration is increased. This sensation can be controlled locally by the device processor **350**, or be controlled by the computer **210**. Local control by the device may eliminate communication burden in some embodiments. Other spatial force sensations besides textures can also be output. In addition, any of the described haptic sensations herein can be output by tactile actuator **260** simultaneously or otherwise combined as desired.

The computer **210** can coordinate haptic sensations with interactions or events occurring within the application program. For example, the tactile mouse **250** may be used as the haptic interface **140** in the simulation system **100** to provide authentic tactile sensations to the user during, in particular, a medical simulation that relates to palpation. The tactile mouse **250** of the present invention can provide tactile sensations that make interaction with the graphical representation **120** more compelling and more intuitive. The user typically controls a cursor **115** to interact with the graphical representation **120**. The cursor **115** may be moved according to a position control paradigm, where the position of the cursor **115** corresponds to a position of the tactile mouse **250** in its planar workspace **205**. Tactile sensations associated with the interaction of the cursor **115** and the graphical representation **120** can be output using the tactile actuator **260**, for example, based on signals output from the local microprocessor **350** or

the computer 210.

5 The simulation system 100 can be designed to provide specific tactile sensations to the user when the simulation system 100 comprises a palpation trainer, such as the palpation trainers discussed above. As a tactile mouse 250 is used to control a cursor 115 in a graphical environment 110 that includes a graphical representation 120 of at least a portion of a living body, such as the graphical environments shown in Figures 1, 2A-2D, 3 and 4, tactile sensations may be output to the housing 215, and thus to the user. In a relatively simple version, a jolt or pop, or other sensation, may be output whenever the cursor 115 intersects the boundary of the graphical representation 120. This version is advantageous in the ease with which it is implementable. This version is advantageous over non-haptic versions in that the user receives tactile input and thus involves more senses in the learning process. In addition, it has been discovered that even simple haptic signals when combined with visual feedback can create a realistic simulation. Thus, when a user views the cursor 115 intersecting the boundary of the graphical representation 120 at the same time that the user feels a tactile sensation, the user believes that the graphical representation has been touched. This effect is even more compelling when the mapping of the cursor 115 is broken so that the cursor 115 appears to rest against the boundary of the graphical representation 120 even though the user object 130 has continued to be moved, as described in U.S. Patent No. 6,028,593 which is incorporated herein by reference in its entirety.

15
20
25
30 A haptic sensation may also be output to the user when the cursor 115 is located within or near a predetermined location on the graphical representation 120. For example, in the version shown in Figure 2A, a jolt or pop may be output to the user when the cursor 115 is within the first region 150 to indicate to the user that the correct location has been found. In a specific version, the first region 150 may relate to the position of the liver for a graphical environment 110 such as the one shown in Figure 4. When the user correctly positions the cursor 115, a haptic sensation is output to indicate that the liver has been located. In the version of Figure 2D, the haptic sensation may also be output when the cursor 115 is within the second region 165. In one version, a first haptic sensation, such as a jolt of a first magnitude, is output when the cursor 115 intersects the graphical representation 120 and a second haptic sensation, such as a second jolt of a different magnitude than the first jolt, is output when the cursor is within the first region 150. Different haptic sensations may be output for each of the different areas of regions of interest in the graphical representation 120.

Vibratory haptic sensations may be output to the user of the simulation system 100. For example, the tactile mouse 250 may be used to simulate the pulse of a living body. In this version, a haptic sensation comprising a low frequency vibration provides a particularly authentic simulation of the pulse. The time-varying force can be output according to a force vs. time waveform that is shaped like a sine wave and may have a frequency of from about .5 Hz to about 3 Hz, depending on the pulse rate that is to be simulated. Vibratory haptic sensations are useful in simulating other experiences taught by the palpation trainer. For example, chest vibrations during talking and breathing, percussion tympani and dullness, and vascular thrill may be simulated by properly adjusting the frequency and magnitude of the vibratory haptic sensation. The vibrations to be output may be determined by performing a vibration analysis on actual patients and using the result to design the output vibrations and/or by having trained medical practitioners evaluate or design the sensations.

The shape of the vibratory waveform may also be selected to provide a predetermined haptic sensation to the user. For example, a sinusoidal waveform may be selected to simulate a healthy pulse. Alternatively, the shape may be other than sinusoidal to indicate an abnormal pulse. To design a complex waveform, the pulse waveform of a diseased patient may be collected and analyzed, for example by performing a Fourier analysis on the signal. The resulting analysis may then be used to create the simulated waveform that is to be output by the simulation system 100. In addition, a display of the waveform, in the time and/or the frequency domains may also be provided.

Texture haptic sensations may also be designed into the simulation system 100. The texture of the skin may be simulated to give the user the sensation of being in contact with the skin. In addition, pops, jolts or vibrations may be added to simulate scars or other features on the surface of the skin. The texture of an internal organ may also be simulated.

Additional haptic sensations that may be provided by the tactile mouse 250 are described in U.S. Patent Application Serial No. 60/224,584, filed on August 11, 2000 and in U.S. Patent Application Serial No. 60/236,417, filed on September 28, 2000.

In another version of the invention the simulation system 100 may comprise a haptic interface 140 comprising a version of a mouse 200 that has kinesthetic force feedback

capabilities. Figure 10 shows a kinesthetic force feedback mouse **400** to which one or more grounded forces may be applied, for example by being applied in the lateral or the x and y directions.

Figure 10 is a perspective view of a kinesthetic force feedback mouse **400** (hereinafter force feedback mouse **400**) as part of a haptic electronic interface **410** according to an embodiment of the present invention. The force feedback mouse **400** in this version is movable in relation to another portion of the interface device **140**.

Force feedback mouse **400** is an object that is preferably grasped or gripped and manipulated by a user. By “grasp,” it is meant that users may releasably engage a portion of the object in some fashion, such as by hand, with their fingertips, etc. For example, images are displayed and/or modified on the display screen **220** of the computer **210** in response to such manipulations. In the described embodiment, force feedback mouse **400** is shaped so that a user’s fingers or hand may comfortably grasp the object and move it in the provided degrees of freedom in physical space. For example, a user can move force feedback mouse **400** to correspondingly move a computer generated graphical object, such as a cursor or other image, in a graphical environment provided by the computer **210**. The available degrees of freedom in which force feedback mouse **400** can be moved are determined from the haptic interface **210**, described below. In addition, force feedback mouse **400** may include one or more buttons **405** to allow the user to provide additional commands to the computer system. The force feedback mouse **400** may also include additional buttons. For example, a thumb button (not shown) may be provided. The buttons allow a user to input a command independently of the position of the force feedback mouse **400** in the provided degrees of freedom, as discussed above. For example, in a GUI, buttons are commonly used to select options once a cursor has been guided to a desired area or object on the screen using the position of the mouse.

Electronic interface **410** interfaces mechanical and electrical input and output between the force feedback mouse **400** and the computer **210** implementing the application program, such as the simulation, a GUI, or game environment. Electronic interface **410** provides multiple degrees of freedom to force feedback mouse **400**; in the preferred embodiment, two linear, planar degrees of freedom are provided to the mouse, as shown by arrows **230**. In other embodiments, greater or fewer degrees of freedom can be provided, as well as rotary degrees of freedom.

In one version, the user manipulates force feedback mouse **400** in a planar workspace, much like a traditional mouse, and the position of force feedback mouse **400** is translated into a form suitable for interpretation by position sensors of the electronic interface **410**. The sensors track the movement of the force feedback mouse **400** in planar space and provide suitable electronic signals to an electronic portion of electronic interface **410**. The electronic interface **410** provides position information to the computer **210**. In addition, the computer **210** and/or electronic interface **410** provide force feedback signals to actuators coupled to electronic interface **410**, and the actuators generate forces on members of the mechanical portion of the electronic interface **410** to provide forces on force feedback mouse **400** in provided or desired degrees of freedom. The user experiences the forces generated on the force feedback mouse **400** as realistic simulations of force sensations such as jolts, springs, textures, “barrier” forces, and the like.

The electronic portion of electronic interface **410** may couple the mechanical portion of the interface to the computer **210**. The electronic portion may be included within the housing **415** of the electronic interface **410** or, alternatively, the electronic portion may be included in the computer **210** or as a separate unit with its own housing. Electronic interface **410** may include a local microprocessor distinct and separate from a microprocessor in the computer **210**. The local microprocessor may be used to control force feedback on force feedback mouse **400** independently of the host computer, as well as sensor and actuator interfaces that convert electrical signals to appropriate forms usable by the mechanical portion of electronic interface **410** and the computer **210**. For example, a rigid surface may be generated on computer screen **220** and a cursor **115** controlled by the user may be caused to interact with, for example by intersecting, the surface. In this embodiment, high-level host commands can be used to provide the various forces associated with the rigid surface. The local control mode using a local microprocessor in electronic interface **410** can be helpful in increasing the response time for forces applied to the user object, which is essential in creating realistic and accurate force feedback. For example, the computer **210** may send a “spatial representation” to the local microprocessor, which is data describing the locations of some or all the graphical objects displayed in a graphical environment **110** which are associated with forces and the types/characteristics of graphical objects, such as a graphical representation **120**, in the graphical environment **110**. The microprocessor can store such a spatial representation in local memory, and thus will be able to determine interactions between the user object and graphical

objects (such as the rigid surface) independently of the computer **210**. In addition, the microprocessor can be provided with the necessary instructions or data to check sensor readings, determine cursor and target positions, and determine output forces independently of the computer **210**. The computer **210** could implement program functions (such as displaying images) when appropriate, and synchronization commands can be communicated between the microprocessor and computer **210** to correlate the microprocessor and computer processes. Also, the local memory can store predetermined force sensations for the microprocessor that are to be associated with particular types of or portions of the graphical representation **120**. Alternatively, the computer **210** can directly send force feedback signals to the electronic interface **410** to generate forces on force feedback mouse **400**.

The electronic interface **410** can be coupled to the computer **210** by a bus **235**, which communicates signals between electronic interface **410** and computer **210** and also may provide power to the electronic interface **410** (e.g. when bus **235** includes a USB interface). In other embodiments, signals can be sent between electronic interface **410** and computer **210** by wireless transmission/reception. In an embodiment of the present invention, the electronic interface **410** serves as an input/output (I/O) device for the computer **210**. The electronic interface **410** can also receive inputs from other input devices or controls that are associated with the haptic interface **140** and can relay those inputs to the computer **210**. For example, commands sent by the user activating a button on force feedback mouse **400** can be relayed to computer **210** by electronic interface **410** to implement a command or cause the computer **210** to output a command to the electronic interface **410**.

There are two primary “control paradigms” of operation for the force feedback mouse **400**: position control and rate control. Position control is the more typical control paradigm for mouse and similar controllers, and refers to a mapping of force feedback mouse **400** in which displacement of the force feedback mouse **400** in physical space directly dictates displacement of the cursor **115**. The mapping can have an arbitrary scale factor or even be non-linear, but the fundamental relation between mouse displacements and graphical object displacements should be present. Under a position control mapping, the cursor **115** does not move unless the force feedback mouse **400** is in motion. Position control is commonly used for medical procedure simulations. Position control force feedback roughly corresponds to forces which would be perceived directly by the user, i.e., they are “user-centric” forces. Also, “ballistics” or other non-linear adjustments to cursor position can be used, in which, for

example, small motions of the mouse have a different scaling factor for cursor movement than large motions of the mouse, to allow more control of small cursor movement. As shown in Figure 10, the computer **210** may have its own “host frame” which is displayed on the display screen **220** and represented by the coordinates u,v . In contrast, the force feedback mouse **400** has its own “local frame” in which the force feedback mouse **400** is moved and represented by coordinates x,y . In a position control paradigm, the position (or change in position) of a user-controlled graphical object, such as a cursor, in host frame corresponds to a position (or change in position) of the force feedback mouse **400** in the local frame. The offset between the object in the host frame and the object in the local frame can be changed by the user. Rate control may also or alternatively be used as a control paradigm. This refers to a mapping in which the displacement of the force feedback mouse **400** along one or more provided degrees of freedom is abstractly mapped to motion of a computer-simulated object under control. There is not a direct physical mapping between physical object (mouse) motion and computer object motion. Thus, most rate control paradigms are fundamentally different from position control in that the user object can be held steady at a given position but the controlled computer object is in motion at a commanded or given velocity, while the position control paradigm only allows the controlled computer object to be in motion if the user object is in motion.

Force feedback mouse **400** may be supported upon a grounded pad **420** which helps define the planar workspace **205**. Pad **420** or a similar surface is supported by grounded surface **425**. Force feedback mouse **400** contacts grounded pad **420** (or alternatively grounded surface **425**) to provide additional support for the mouse and relieve stress on any mechanical support structures.

The haptic interface comprising a force feedback mouse may also include an indexing function or “indexing mode” which allows the user to redefine the offset between the positions of the force feedback mouse **400** in the local frame and a cursor **115**, in the host frame displayed by the computer **210**. Indexing is inherently provided with a traditional position control device such as a standard mouse. When a physical limit to the mouse’s movement is reached, the user typically lifts the mouse from the contacted surface and places the mouse in a different position to allow more room to move the mouse. While the mouse is off the contacted surface, no input is provided to control the cursor. Force feedback mouse **400** of the present invention also has a limit to movement in the provided planar workspace provided by a guide opening, as detailed below. To allow movement of the cursor in the host frame past the limits

of the mouse local frame, "indexing" is implemented. In one implementation, the user may reposition the force feedback mouse **400** without moving the controlled graphical object or providing any other input to the host computer, thus allowing the user to redefine the offset between the object's position and the cursor's position. This is analogous to standard mouse indexing. In the present invention, such indexing is achieved through an input device such as button **405**, or alternatively using switches, pressure sensors, optical sensors, contact sensors, voice recognition hardware, or other input devices. As long as the indexing button or device is activated, the force feedback mouse **400** is in indexing mode and can be moved without providing any input to the host computer (e.g., without moving the controlled graphical object). When the button is released (or indexing mode otherwise exited), the position of the cursor is again controlled by the position of the force feedback mouse **400**. Alternatively, the user might toggle indexing mode and non-indexing mode with one press of a button **405** or other input device. Indexing mode can be performed directly by the computer **210**, or a local microprocessor can perform the indexing function. For example, the local processor can determine when indexing mode is active, and simply not report the position of the force feedback mouse **400** to the the computer **210** while such mode is active. A hand weight switch may also be provided for indexing purposes, as described in U.S. Patents 5,825,308 and 6,100,874, both of which are incorporated herein by reference in their entireties.

Figure 11a is a perspective view of an embodiment of the haptic interface **140** with the cover portion of housing **415** and the grounded pad **420** removed. Force feedback mouse **400** is coupled to a mechanical interface **430**, which includes a mechanical linkage **435** that is coupled to a transducer assembly **440**. A base **445** is provided to support the mechanical linkage **435** and transducer assembly **440** on grounded surface **425**. In the described embodiment, the linkage **435** allows force feedback mouse **400** two planar degrees of freedom in the directions of arrows **230**, and the members of the linkage **435** move approximately within a plane. The linkage is preferably coupled to grounded base **445** at an axis of rotation, described below. The transducer assembly **440** is coupled to base **445** and is thus also grounded.

In the described embodiment, at least part of the electronic interface **410** is positioned above the transducer assembly **440**. For example, a printed circuit board **450** or similar support can be positioned over the top surface of transducer assembly **440**. A number of integrated circuits and other components **455** can be coupled to the printed circuit board **450**.

This configuration allows the transducer assembly **440** and the electronic interface **410** to conform to a small volume which reduces the overall size of housing **415** and allows the mouse interface device to be positioned in convenient areas of a desktop or other area accessible to a user.

5

Figure 11b is a perspective view of a portion of the mouse device **11** of Figure 2a showing the mechanical interface **430** for providing mechanical input and output in accordance with the present invention. Mechanical linkage **435** provides support for force feedback mouse **400** and couples the mouse to a grounded surface **425**, such as a tabletop or other support.

10 Linkage **435** is, in the described embodiment, a 5-member (or "5-bar") linkage including a base **445**, a first base member **460** coupled to base **445**, a second base member **465** coupled to base **445**, a first link member **470** coupled to first base member **460**, and a second link member **475** coupled to first link member **470** and second base member **465**. In the described embodiment, the first base member **460** and the first link member **470** are arranged generally symmetric to the second base member **465** and the second link member **475** across an axis extending perpendicularly through axes A and D. The symmetrical orientation of the members allows first base member **460** and first link member **470**, in some embodiments, to be manufactured substantially in identical fashion as second base member **465** and second link member **475**, thus saving on manufacturing costs. Force feedback mouse **400** is coupled to the linkage at the coupling between link members **470**, **475**. Fewer or greater numbers of members in the linkage can be provided in alternate embodiments. Base **445** of the linkage **435** is a base for the support of the linkage and is coupled to or resting on a ground surface **425**. The base **445** in Figure 11b is shown as a plate or base that extends under force feedback mouse **400**.

25 The members of linkage **435** are rotatably coupled to one another through the use of rotatable pivots or bearing assemblies having one or more bearings, all referred to as "bearings" herein. Linkage **435** is rotatably coupled to base **445** by a grounded bearing **480** and can rotate about an axis A. First link member **470** is rotatably coupled to first base member **460** by bearing **485** and can rotate about a floating axis B, and first base member **465** is rotatably coupled to base **445** by bearing **480** and can rotate about axis A. Second link member **475** is 30 rotatably coupled to second base member **465** by bearing **490** and can rotate about floating axis C, and second link member **475** is also rotatably coupled to first link member **470** by bearing **495** such that second link member **475** and first link member **470** may rotate relative to each other about floating axis D. In an alternate embodiment, a parallel linkage may be used as

disclosed in U.S Patent 6,100,874, which is incorporated herein by reference in its entirety. The axes B, C, and D are “floating” in the sense that they are not fixed in one position relative to ground surface **425** as is axis A. Since the only connection of the four linkage members to the base **445** is through grounded bearing **480**, only base members **460**, **465** are grounded at axis A. Bearings **485**, **490**, and **495** are floating and not connected to the ground member. Preferably, the axes B, C, and D are all substantially parallel to each other.

Linkage **435** is formed as a five-member closed-loop chain. Each member in the chain is rotatably coupled to two other members of the chain. The five-member linkage is arranged such that the members can rotate about their respective axes to provide force feedback mouse **400** with two degrees of freedom, i.e., force feedback mouse **400** can be moved within a planar workspace defined by the x-y plane, which is defined by the x- and y-axes as shown in Figure 11b. Linkage **435** is thus a “planar” five-member linkage, since it allows the force feedback mouse **400** to be moved within a plane. In addition, in the described embodiment, the members of linkage **435** are themselves approximately oriented in a plane.

Force feedback mouse **400** in this embodiment is coupled to link members **470**, **475** by rotary bearing **495**, for example at attachment plate **500**. The mouse may also preferably rotate about floating axis D and allow the user some flexible movement in the planar workspace. The allowed rotation can provided to allow the user’s hand/wrist to conveniently stay in one position during mouse movement while the force feedback mouse **400** rotates about axis D. In alternate embodiments, mouse rotation about axis D may be sensed by sensors. In yet other embodiments, forces can be provided on force feedback mouse **400** about axis D using actuators. In the preferred embodiment, a pad or other support is provided under force feedback mouse **400** to help support the force feedback mouse **400**, and is described in greater detail with respect to Figure 11c.

Transducer assembly **440** is used to sense the position of force feedback mouse **400** in its workspace and to generate forces on the force feedback mouse **400**. Transducer assembly **440** may include one or more sensors **505a**, **505b** and/or one or more actuators **510a**, **510b**. The sensors **505a**, **505b** collectively sense the movement of the force feedback mouse **400** in the provided degrees of freedom and send appropriate signals to the electronic interface **410**. Sensor **505a** senses movement of second base member **465** about axis A, and sensor **505b** senses movement of first base member **460** about axis A. These sensed positions about axis A

allow the determination of the position of force feedback mouse **400** using known constants such as the lengths of the members of linkage **435** and using well-known coordinate transformations. Member lengths particular to the interface device can be stored in a memory, such as EEPROM, to account for manufacturing variations among different interface devices; alternatively, variations of the particular link lengths from standard lengths can be stored in memory.

Sensors **505a**, **505b** are, in the described embodiment, grounded optical encoders that sense the intermittent blockage of an emitted beam. A grounded emitter/detector portion **515** includes an emitter that emits a beam which is detected by a grounded detector. A moving encoder disk portion or “arc” is provided at the end of members **460**, **468** which each block the beam for the respective sensor in predetermined spatial increments and allows a processor to determine the position of the arc and thus the members **460**, **465** by counting the spatial increments. Also, a velocity of members **460**, **465** based on the speed of passing encoder marks can also be determined. In one embodiment, dedicated electronics such as a “haptic accelerator” may determine velocity and/or acceleration, as disclosed in U.S. Patent 5,999,168 which is incorporated herein by reference in its entirety. and hereby incorporated by reference herein.

In the version shown, transducer assembly **440** also includes actuators **510a**, **510b** to transmit forces to force feedback mouse **400** in space, i.e., in two (or more) degrees of freedom of the user object. The bottom housing plate **520** of actuator **510a** is rigidly coupled to base **445** (or grounded surface **425**) and a moving portion of actuator **510a** (for example a coil) is integrated into the base **445**. The actuator **510a** transmits rotational forces to first base member **460** about axis A. The housing **520** of the grounded portion of actuator **510b** is rigidly coupled to base **445** or ground surface **425** through the grounded housing of actuator **510b**, and a moving portion (for example a coil) of actuator **510b** is integrated into second base member **465**. Actuator **510b** transmits rotational forces to second base member **465** about axis A. The combination of these rotational forces about axis A allows forces to be transmitted to force feedback mouse **400** in all directions in the planar workspace provided by linkage **435** through the rotational interaction of the members of linkage **435**.

The operation of exemplary sensors **505a**, **505b** and actuators **510a**, **510b** are described in greater detail in U.S. Patents 5,166,723 and 5,100,874, both of which are

incorporated herein by reference in their entireties. Additional and/or different mechanisms can also be employed to provide desired degrees of freedom to force feedback mouse **400**. This rotational degree of freedom can also be sensed and/or actuated, if desired, to provide an additional control degree of freedom. In other embodiments, a floating gimbal mechanism can be included between force feedback mouse **400** and linkage **435** to provide additional degrees of freedom to force feedback mouse **400**. Optionally, additional transducers can be also added to electronic interface **410** in provided or additional degrees of freedom of force feedback mouse **400**. In an alternate embodiment, the mechanism can be used for a 3-D interface device that allows a user to move a user object in three dimensions rather than the 2-D planar workspace disclosed. For example, in one embodiment, the entire mechanism can be made to rotate about a grounded axis, such as axis H extending through the actuators **510**. For example, members (not shown) rigidly coupled to the actuators **510** or to base **445** can extend in both directions along axis H and be rotary coupled to a grounded surface at points H1 and H2. This provides a third (rotary) degree of freedom about axis H. A motor can be grounded to the surface near point H1 or H2 and can drive the mechanism about axis H, and a sensor, such as a rotary encoder, can sense motion in this third degree of freedom. One reason for providing axis H through the magnet assemblies is to reduce the inertia and weight contributed to motion about axis H by the magnet assemblies. Axis H can be provided in other positions in other embodiments. In such an embodiment, the user object **130** can be a stylus, grip, or other user object. A third linear degree of freedom to mechanism can be provided in alternate embodiments. One embodiment of a planar linkage providing three degrees of freedom is disclosed in co-pending patent application serial no. 08/736,161 filed 10/25/96 and hereby incorporated by reference herein.

Figure 11c is a perspective view of the grounded pad **420** and electronic interface **410** of the mouse system, where the force feedback mouse **400** has been detached from the mechanical linkage **435**. As shown, pad **420** preferably has a height h and may be hollow to allow the mechanical linkage **435** to be positioned underneath the top surface of the pad **420**. The bearing **495** may be arranged to extend through a guide opening **525** in the pad **420**. An attachment plate **500** can be coupled to the bearing **495** or rotatably coupled to a member of linkage **435** to provide a point for attaching the force feedback mouse **400** to the linkage **435**. In one version, the force feedback mouse **400** is releasably coupled to attachment plate **500**. In the described embodiment, the opening **525** provides the limits to the workspace of the force feedback mouse **400**. Bearing **495** and plate **500** protrude through opening **525** such that a

rounded portion of plate **500** (provided under the flat plate portion), when moved in any degree of freedom of the force feedback mouse **400**, eventually impacts a side of opening **525**. The four sides to the opening **525** thus provide limits to the workspace of the force feedback mouse **400** in the provided planar degrees of freedom, i.e., a stop mechanism is provided that limits the movement of the force feedback mouse **400** as defined by the size of opening **525**. Opening **525** can be made any size desired. For example, in the described embodiment, opening **525** has relatively small dimensions, such as approximately 1 3/8" by 1 1/8". The size of the opening **525** is larger than the workspace of the mouse due to the size or radius of the rounded portion; thus, with the described opening size, a workspace of about 1" by 3/4" is obtained for the force feedback mouse **400** (which is considered at the center of bearing **495** at axis D). This is typically adequate workspace for the user to move the mouse and control a graphical object such as a cursor **115** on a display screen. In addition, this size workspace has an aspect ratio of 4:3, which is about the aspect ratio of a standard computer monitor, television, or other display screen. An aperture **530** can also be provided to route wires or cables from buttons, for example, on the mouse to the electronic interface **410**. Alternatively, an inductive coil can be included in force feedback mouse **400** to transmit a signal when a button is activated, where the signal is received by another inductive coil in pad **420** which detects the activation of buttons, the operation of such coils being well known to those skilled in the art. Other wireless devices can also be used.

The top surface of grounded pad **420** may be a smooth material, such as a smooth slick plastic, to allow contact with portions of force feedback mouse **400**. Such contact provides support for force feedback mouse **400** when the mouse is moved in its planar workspace and allows the mouse to slide on the pad **420** with little friction. Since the linkage **435**, when extended, is cantilevered at a large moment arm, a small force at the mouse end of the linkage can create a large torque that stresses the mounting or coupling **480** at axis A, which may use the mounting or coupling to bend. Pad **420** thus balances the cantilever load by providing support to any pressure or force from the user in the z-direction on force feedback mouse **400** toward the ground surface **425**.

Figure 12 is a block diagram illustrating a version of the haptic interface **140** comprising an electronic interface **410** and a mechanical interface **430** usable with the version of the invention shown in Figures 10, and 11a-11c. The simulation system **100** includes a computer **210** and the haptic interface **140**. The computer **210** may include a host

microprocessor **540**, random access memory (RAM) **545**, read-only memory (ROM) **550**, input/output (I/O) electronics **555**, a clock **560**, a display device **220**, and an audio output device **565**. Host microprocessor **540** can include a variety of available microprocessors from Intel, AMD, Motorola, or other manufacturers. Host microprocessor **540** can be single
 5 microprocessor chip, or can include multiple primary and/or co-processors. Host microprocessor **540** preferably retrieves and stores instructions and other necessary data from RAM **545** and ROM **550** as is well known to those skilled in the art. In the described embodiment, the computer **210** can receive sensor data or a sensor signal via a bus **235**. Host microprocessor **540** can receive data from bus **235** using I/O electronics **555**, and can use I/O
 10 electronics to control other peripheral devices. The computer **210** can also output commands to haptic interface device **140** via bus **235** to cause force feedback for the simulation system **100**.

Clock **560** is a standard clock crystal or equivalent component used by the computer **210** to provide timing to electrical signals used by host microprocessor **540** and other components of the computer **210**. Clock **560** is accessed by the computer **210** in the control
 5 process of the present invention to provide timing information that may be necessary in determining force or position, e.g., calculating a velocity or acceleration from position values.

Display device **220** is similar to that described above. Audio output device **565**, such as speakers, can be coupled to host microprocessor **540** via amplifiers, filters, and other circuitry well known to those skilled in the art. Host processor **540** outputs signals to speakers
 10 **565** to provide sound output to the user when an “audio event” occurs during the implementation of the host application program. Other types of peripherals can also be coupled to host processor **540**, such as storage devices (hard disk drive, CD ROM drive, floppy disk drive, etc.), printers, and other input and output devices.
 25

Haptic interface **140** includes an electronic interface **410** and a mechanical interface **430** (which each may include both electronic and mechanical components). The electronic interface **410** is coupled to the computer **210** by a bi-directional bus **235**. The bi-
 30 directional bus **235** sends signals in either direction between the computer **210** and the interface device **140**. Bus **235** can be a serial interface bus, as discussed above. A USB may serve as the serial interface bus to also source power to drive actuators **510** and other devices. Since each device that accesses the USB is assigned a unique USB address by the computer **210**, this allows multiple devices to share the same bus. In addition, the USB standard includes timing

data that is encoded along with differential data.

The Electronic interface **410** includes a local microprocessor **570**, local clock **575**, local memory **580**, sensor interface **585**, and actuator interface **590**. Electronic interface **410** may also include additional electronic components for communicating via standard protocols on bus **235**. In various embodiments, electronic interface **410** can be included in mechanical interface **430**, in the computer **210**, or in its own separate housing. Different components of electronic interface **410** can be included in interface **430** or the computer **210** if desired.

Local microprocessor **570** may be coupled to bus **235** and may be closely linked to mechanical interface **430** to allow quick communication with other components of the interface device. Processor **570** is considered “local” to haptic interface **140**, where “local” herein refers to processor **570** being a separate processor, such as a microprocessor, from a processor **540** in the computer **210**. “Local” may also refer to processor **570** being dedicated to force feedback and sensor I/O of the haptic interface **140**, and being closely coupled to sensors and actuators of the mechanical interface **430**, such as within the housing of or in a housing coupled closely to interface **430**. Microprocessor **570** can be provided with software instructions to wait for commands or requests from the computer **210**, parse/decode the command or request, and handle/control input and output signals according to the command or request. In addition, processor **570** may operate independently of the computer **210** by reading sensor signals and calculating appropriate forces from those sensor signals, time signals, and force processes selected in accordance with a host command, and output appropriate control signals to the actuators. Suitable microprocessors for use as local microprocessor **570** include the MC68HC711E9 by Motorola and the PIC16C74 by Microchip, for example. Microprocessor **570** can include one microprocessor chip, or multiple processors and/or co-processor chips. In other embodiments, microprocessor **570** can include digital signal processor (DSP) functionality.

For example, in one host-controlled embodiment that utilizes a local microprocessor **570**, the computer **210** can provide low-level force commands over bus **235**, which microprocessor **570** directly transmits to the actuators **510**. In a different local control embodiment, the computer **210** provides high level supervisory commands to microprocessor **570** over bus **235**, and microprocessor **570** manages low level force control loops to sensors and

actuators in accordance with the high level commands and independently of the computer **210**. In the local control embodiment, the microprocessor **570** can process inputted sensor signals to determine appropriate output actuator signals by following the instructions of a “force process” that may be stored in local memory and includes calculation instructions, formulas, force magnitudes, or other data. The force process can command distinct force sensations, such as vibrations, textures, jolts, or kinesthetic forces simulating interactions between displayed objects in the graphical environment **110**. An “enclosure” host command can also be provided, which causes the microprocessor **570** to define a box-like enclosure in a graphical environment **110**, where the enclosure has sides characterized by wall and texture forces, as described in U.S. Patent 6,100,874. The computer **210** can send the local processor **570** a spatial layout of objects, such as a graphical representation **120** in the graphical environment **110** so that the microprocessor **570** has a mapping of locations of graphical objects like enclosures and can determine interactions with the cursor **115** locally. Force feedback used in graphical environments is described in greater detail in U.S. Patents 5,629,594 and 5,825,308, both of which are incorporated by reference herein.

Sensor signals used by microprocessor **570** are also reported to the computer **210**, which updates a host application program and outputs force control signals as appropriate. For example, if the user moves force feedback mouse **400**, the computer **210** receives position and/or other signals indicating this movement or manipulation of the user object **130** and can move a displayed cursor **115** in response. In an alternate embodiment, no local microprocessor is included in the haptic interface **140**, and the computer **210** directly controls and processes all signals to and from the electronic interface **410** and mechanical interface **430**.

A local clock **575** can be coupled to the microprocessor **570** to provide timing data, similar to system clock **560** of the computer **210**; the timing data might be required, for example, to compute forces output by actuators **510** (e.g., forces dependent on calculated velocities or other time dependent factors). In alternate embodiments using the USB communication interface, timing data for microprocessor **570** can be retrieved from the USB interface. Local memory **580**, such as RAM and/or ROM, may be coupled to microprocessor **570** in to store instructions for microprocessor **570** and store temporary and other data. Microprocessor **570** may also store calibration parameters in a local memory **580** such as an EEPROM. As described above, link or member lengths or manufacturing variations and/or variations in coil winding or magnet strength can be stored. If analog sensors are used,

adjustments to compensate for sensor variations can be included, e.g. implemented as a look up table for sensor variation over the user object workspace. Memory **580** may be used to store the state of the force feedback device, including a reference position, current control mode or configuration, etc.

5

Sensor interface **585** may optionally be included in electronic interface **410** to convert sensor signals to signals that can be interpreted by the microprocessor **570** and/or the computer **210**. For example, sensor interface **585** can receive signals from a digital sensor such as an encoder and convert the signals into a digital binary number representing the position of a member or component of mechanical apparatus **430**. An analog to digital converter (ADC) in sensor interface **585** can convert a received analog signal to a digital signal for microprocessor **570** and/or the computer **210**. Such circuits, or equivalent circuits, are well known to those skilled in the art. Alternately, microprocessor **570** can perform these interface functions without the need for a separate sensor interface **585**. Alternatively, sensor signals from the sensors **505** can be provided directly to the computer **210**, bypassing microprocessor **570** and sensor interface **585**. Other types of interface circuitry can also be used.

10

15

Actuator interface **590** can be optionally connected between the actuators **510** and microprocessor **570**. Actuator interface **590** converts signals from microprocessor **570** into signals appropriate to drive the actuators. Actuator interface **590** can include power amplifiers, switches, digital to analog controllers (DACs), and other components. Such interfaces are well known to those skilled in the art. In alternate embodiments, actuator interface **570** circuitry can be provided within microprocessor **570** or in the actuators **510**.

20

25

In the described embodiment, power is supplied to the actuators **510** and any other components (as required) by the USB. Since the electromagnetic actuators of the described embodiment have a limited physical range and need only output, for example, about 3 ounces of force to create realistic force sensations on the user, very little power is needed. A large power supply thus need not be included in interface system or as an external power adapter. For example, one way to draw additional power from the USB is to the haptic interface **140** to appear as more than one peripheral to the computer **210**; for example, each provided degree of freedom of force feedback mouse **400** can be configured as a different peripheral and receive its own allocation of power. Alternatively, power from the USB can be stored and regulated and thus used when needed to drive actuators **510**. For example, power

30

can be stored over time and then immediately dissipated to provide a jolt force to the user object **130**. A battery or a capacitor circuit, for example, can store energy and discharge or dissipate the energy when power is required by the system and/or when enough power has been stored. Alternatively, a power supply **595** can optionally be coupled to actuator interface **590** and/or actuators **510** to provide electrical power. Power supply **595** can be included within the housing of the haptic interface device **140**, or can be provided as a separate component, for example, connected by an electrical power cord. The power storage embodiment described above, using a battery or capacitor circuit, can also be used in non-USB embodiments to allow a smaller power supply **595** to be used.

Mechanical interface **430** is coupled to the electronic interface **410** and may include sensors **505**, actuators **510**, and linkage **435**. These components are described in detail above. Sensors **505** sense the position, motion, and/or other characteristics of force feedback mouse **400** along one or more degrees of freedom and provide signals to microprocessor **570** including information representative of those characteristics. Typically, a sensor **505** is provided for each degree of freedom along which force feedback mouse **400** can be moved, or, a single compound sensor can be used for multiple degrees of freedom. Example of sensors suitable for embodiments described herein are optical encoders, as described above. Linear optical encoders may similarly sense the change in position of force feedback mouse **400** along a linear degree of freedom. Alternatively, analog sensors such as potentiometers can be used. It is also possible to use non-contact sensors at different positions relative to mechanical interface **430**, such as Hall effect magnetic sensors for detecting magnetic fields from objects, or an optical sensor such as a lateral effect photo diode having an emitter/detector pair. In addition, velocity sensors (e.g., tachometers) for measuring velocity of force feedback mouse **400** and/or acceleration sensors (e.g., accelerometers) for measuring acceleration of force feedback mouse **400** can be used. Furthermore, either relative or absolute sensors can be employed.

Actuators **510** transmit forces to force feedback mouse **400** in one or more directions along one or more degrees of freedom in response to signals output by microprocessor **570** and/or the computer **210**, i.e., they are “computer controlled.” Typically, an actuator **510** is provided for each degree of freedom along which forces are desired to be transmitted. Actuators **510** can include active actuators, such as linear current control motors, stepper motors, pneumatic/hydraulic active actuators, a torquer (motor with limited angular range), a voice coil actuator as described in the embodiments above, and/or other types of

actuators that transmit a force to an object. Passive actuators can include magnetic particle brakes, friction brakes, or pneumatic/hydraulic passive actuators, and generate a damping resistance or friction in a degree of motion. For example, an electrorheological fluid can be used in a passive damper, which is a fluid that has a viscosity that can be changed by an electric field. Likewise, a magnetorheological fluid can be used in a passive damper, which is a fluid that has a viscosity that can be changed by a magnetic field. These types of dampers can be used instead of or in addition to other types of actuators in the mouse interface device. In yet other embodiments, passive damper elements can be provided on the bearings of interface **430** to remove energy from the system and intentionally increase the dynamic stability of the mechanical system. In addition, in voice coil embodiments, multiple wire coils can be provided, where some of the coils can be used to provide back EMF and damping forces. In some embodiments, all or some of sensors **505** and actuators **510** can be included together as a sensor/actuator pair transducer.

The mechanism **435** may be the five-member linkage **435** described above, but can also be one of several types of mechanisms. Force feedback mouse **400** can alternatively be a puck, joystick, or other device or article coupled to linkage **435**, as described above.

Other input devices **600** can optionally be included in system **100** and send input signals to microprocessor **570** and/or the computer **210**. Such input devices can include buttons, such as buttons **405** on force feedback mouse **400**, used to supplement the input from the user to a simulation, GUI, game, etc. Also, dials, switches, voice recognition hardware (with software implemented by computer **210**), or other input mechanisms can be used.

Safety or “deadman” switch **605** may be included in haptic interface device **140** to provide a mechanism to allow a user to override and deactivate actuators **510**, or require a user to activate actuators **510**, for safety reasons, as discussed above.

Haptic sensations may be designed to be output by the force feedback mouse **400** in association with, for example, a palpation simulation being performed with the simulation system **100**. For example, all of the tactile sensations discussed above in connection with the tactile mouse **250** can be output by the force feedback mouse **400**. For example, a desired vibration may be output to simulate a pulse or other vibration to be simulated.

In addition, the force feedback mouse 400 may output grounded lateral forces to provide kinesthetic force simulation of the interaction of the cursor 115 with the graphical representation 120. For example, a barrier force may be associated with the boundary of the graphical representation 120. When the cursor 115 intersects the boundary of the graphical representation 120, a spring force, for example may be output to the force feedback mouse 400 inhibiting movement of the force feedback mouse 400 in the direction of the graphical image 120. A high value may be selected for the spring constant to simulate a hard object that can not be easily penetrated, and a lower value may be selected to simulate softer surfaces. Additionally or alternatively, a constant or a substantially constant force may be applied to the force feedback mouse 400 to simulate a variety of events, such as the friction of skidding the cursor 115 across the graphical representation 120.

The force feedback mouse 400 is also particularly advantageous in simulating the three dimensional surface contour of the graphical representation 120. A three dimensional mouse may output barrier forces in three dimensions to give a precise haptic simulation of the three dimensional contour of a graphical representation 120. Alternatively, and unexpectedly, a two-dimensional force feedback mouse 400, such as the version of Figure 10, may output lateral forces to allow the user to feel the three dimensional contour of the graphical representation 120. This can be achieved, for example, using spring forces or constant forces to make the user perceive a z-axis contour. Figures 13A-D schematically illustrate the forces to be output in order to simulate the three dimensional contour. Figure 13A shows the cross-section, for example in the x,z plane, of a graphical representation 120. This cross-section would typically not be displayed on the screen 220 but is shown in Figure 13A to illustrate the force effects and force profile associated with the surface of the representation. A geometrical model similar to the one shown in Figure 13A could be used to approximate a patient's wrist, for example. As a cursor 115 is moved from the position shown in Figure 13A along the x-axis, it will intersect the graphical representation 130. Figure 13B shows a force profile that may be output to the force feedback mouse 400 as a function of the position of the cursor 115 in relation to the graphical representation 120. Before the cursor 115 reaches the graphical representation 120, that is when the cursor 115 is positioned to the left of point a, there is no force output to the user. In the position between points a and b in the x axis, a constant force in the negative x direction is output to simulate the force required to climb the slope of the edge of the graphical representation 120. When the cursor 115 is positioned at an x-axis position corresponding to the top portion from points b to c, no force is output. Alternatively, a small negative force, such

as a force equal to about ten percent of the force applied between points a and b, may be output to simulate friction along the surface or haptic sensations such as pops may be output to simulate the texture of the surface. As the cursor 115 reaches point c, a positive force, optionally of the same but opposite value as the previously applied force, is then output to simulate the cursor 115 falling down the slope from points c to d. After point d, the force is released. This simulation can be effective in making the user perceive that a bump or other contour was felt, especially when combined with a breaking of the mapping of the display of the cursor 115 in relation to the graphical representation 120, as shown by broken map cursor 115'. Figure 13C shows a rounded depression that may also be simulated. Due to the rounded nature of the sides of the contour, the magnitude of the applied force is greatest at points e and g of the contour. Figure 13D shows a force profile that may be used to simulate the contour of Figure 13C.

This modeling can be extended to a graphical representation of an entire portion of a body or to an entire body to allow the user to haptically interact with the graphical representation during palpation training. In this way surface features, such as ribs, bones, breasts, scars, fatty deposits, a navel, etc. can be felt by the user. For example, a the contour of a breast may be simulated with a 2-dimensional device, as shown in Figures 14A and 14B. This is accomplished by superimposing the surface contour simulation of a smaller portion of the graphical representation 120 over the surface contour simulation of a larger portion of the graphical representation 120, as shown.

In addition, features beneath the surface of the graphical representation 120 may be felt. In a simple version, force related to the underlying feature may be output when the cursor 115 is in the correct location within the graphical representation 120. For example, the simulation system 100 may task the user to locate the liver. Once the cursor is located at a position for proper palpation of the liver, subsequent movement of the cursor 115 may be caused by the simulation system 100 to appear as though the surface is being depressed and contour related force may be output based on the position of the cursor 115 (or based on the position of the user object 130). In another version, a force sensor may be included in the mouse 400 (or in another user object 130), and the user must press against the mouse 400 in order to cause the cursor 115 to be depressed into the graphical representation 120 (which may be displayed as a broken mapped cursor 115'). In this version, the contour forces may be output based on position and force. Accordingly, a user who has merely properly located the cursor

over the liver, but who is not pressing into the body, will not feel the liver. Similarly, the user who is pressing too hard into the body may not be able to feel the liver and may receive an indication from the simulation system **100** that the patient is being injured or is uncomfortable. This version is shown schematically in Figures 15A through 15D. Figure 15A shows a graphical representation **120** having a surface on which rests a cursor **115**. Under the surface is a feature, such as a trapezoidal geometric model of a liver, which may be shown on the display, shown in phantom on the display, or not shown. The user must exert a z-axis force on the mouse **400** in order to simulate pressing into the surface. In one version, the mapping of the cursor is broken and the cursor **115'** penetrates the surface in the z-direction as a function of the z-axis force applied by the user. When an insufficient z-axis force, F_z , has been applied, the user will receive no force simulation of an underlying feature, as shown by the force profile shown in Figure 15B, where F_z is less than a first threshold, $FT1$. When the z-axis force, F_z , is above the first threshold, $FT1$, a force profile according to Figure 15C, for example, will be output to the user to simulate the feel of the underlying feature. Optionally, a second threshold, $FT2$, may also be provided and the force profile may be altered when the second threshold, $FT2$, is exceeded. In the version shown in Figure 15D, the force profile is a muted version of the force profile for appropriate force values. Additionally, the other indications, such as visual or audible indications, may be provided to inform the user that too much force has been applied. The force sensor may be embodied as part of a safety switch or may be a separate force sensor, for example of the piezo electric or strain gage type, as described in U.S. Patent 6,100,874 which is incorporated herein by reference in its entirety.

In another and more advanced version of the invention, a coordinate transformation may be approximated to simulate three dimensional contour using a two-dimensional input device, such as the force feedback mouse **400**. For example, the user's z-axis may be transformed into the graphical environment **110**. The intersection of the transformed z-axis with the graphical representation **120** may then be determined. A unit vector normal to the graphical representation **120** at the intersection may then be computed. This unit vector may then be transformed back to the user's coordinates, scaled and output to the user.

It will be appreciated that a great number of other types of haptic interface devices **140** and/or user objects **130** can be used with the method and apparatus of the present invention, some of which are discussed above. For example, handheld devices are very suitable for the actuator assemblies described herein. A hand-held remote control device used to select

functions of a television, video cassette recorder, sound stereo, internet or network computer (e.g., Web-TV™), or a gamepad controller for video games or computer games, can be used with the haptic feedback components described herein. Handheld devices are not constrained to a planar workspace like a mouse but can still benefit from the directed inertial sensations and contact forces described herein which, for example, can be output about perpendicularly to the device's housing surfaces. Other interface devices may also make use of the actuator assemblies described herein. For example, a joystick handle can include the actuator assembly, where haptic sensations are output on the joystick handle as the sole haptic feedback or to supplement kinesthetic force feedback in the degrees of freedom of the joystick. Trackballs, steering wheels, styluses, rotary knobs, linear sliders, gun-shaped targeting devices, medical devices, grips, etc. can also make use of the actuator assemblies described herein to provide haptic sensations. The haptic interface may comprise a gamepad type device, a remote control device, a PDA, or a touchpad or tactile display. In one version, a haptic touchpad, such as the one described in co-pending Patent Application Serial No. 09/487,737 filed on January 19, 2000, which is incorporated herein by reference in its entirety. In this version, the touchpad may be incorporated into or used with a lap-top computer. Accordingly, the entire simulation system **100** may be housed within the lap-top computer.

In another version, as shown in Figure 16, a mouse **200**, or other user object **130** comprises a finger receiving member **610**. In the version shown, a first finger receiving recess or channel **615** is positioned adjacent to a second finger receiving recess or channel **620**. Using this version, a user may control the movement of the cursor **115** using only his or her fingers. This provides a particularly realistic simulation when the cursor **115** is representative of the user's fingers, as shown for example in the version of Figure 3. This version is also advantageous in that the haptic sensations are applied directly to the fingers of the user in much the same manner as the user would experience the sensations in an actual procedure. Alternatively, one finger receiving recess or channel may be provided, or more than two, such as five, may be provided. The recess or channel may be a trough, as shown, or may be a recess in the housing of the mouse **200**, or may be in the form of a cylindrical or conical cuff that encircles one or more fingers. The recesses or channels may be positioned on the mouse **200** in a manner to allow the buttons to be depressed. For example, the recess or channel may be flexible, may include an opening through which the finger may contact a button, or may terminate short of a button to allow a user to access the button. Alternatively, the mouse **200** may not include buttons.

An application program, such as a palpation simulation program may be stored in a computer readable format on a computer readable medium. For example a computer readable medium may comprising a computer readable program including program instructions to cause a palpation simulation to be executed on the computer. The computer readable medium may comprise one or more of as memory in the computer, a magnetic disk or tape, a compact disk, a digital video disk, or the like. In one version, the computer readable program may be downloaded to the computer from a remote source via a networked connection.

In one version of the invention, a networked connection may be provided, for example as described in U.S. Patent Application 09/153,781 filed on September 16, 1998, which is incorporated herein by reference in its entirety. In this version, a user may download an application program, such as a palpation simulation program, or a file of haptic sensations from a remote location. Also, a user may interact with a simulation running at a remote location. In another version, the haptic interface may be used as a master device to control a remote slave device. The slave device may be representative of the user's hand or fingers for example, and the user may control the slave to, for example, perform a palpation procedure on a remote patient. In an advanced version, the slave device may be equipped with sensors to detect conditions of the slave device, such as pressures or forces. The sensed conditions may then be used to provide haptic sensations to the user via the master device, the haptic sensations being related to the sensed conditions of the slave device.

While this invention has been described in terms of several preferred embodiments, it is contemplated that alterations, permutations and equivalents thereof will become apparent to those skilled in the art upon a reading of the specification and study of the drawings. For example, many different types of haptic sensations can be provided with the haptic interface of the present invention and many different types actuators and user objects can be used. In addition, the haptic interface can be replaced by a non-haptic interface, for example, when the mapping of the cursor is broken. Furthermore, certain terminology, such as terms like x, y, z, left, right, up, down, etc., has been used for the purposes of descriptive clarity, and not to limit the present invention. Therefore, the appended claims should not be limited to the description of the preferred versions contained herein and should include all such alterations, permutations, and equivalents as fall within the true spirit and scope of the present invention.